



ΠΑΝΕΠΙΣΤΗΜΙΟ ΠΕΙΡΑΙΩΣ

UNIVERSITY OF PIRAEUS

ΤΜΗΜΑ ΝΑΥΤΙΛΙΑΚΩΝ ΣΠΟΥΔΩΝ

**ΠΡΟΓΡΑΜΜΑ ΜΕΤΑΠΤΥΧΙΑΚΩΝ
ΣΠΟΥΔΩΝ ΣΤΗ ΝΑΥΤΙΛΙΑ**

TRANSITION TO DECARBONISATION

Τσαγγούρης Σαράντος

Διπλωματική Εργασία

που υποβλήθηκε στο Τμήμα Ναυτιλιακών Σπουδών του Πανεπιστημίου Πειραιώς ως
μέρος των απαιτήσεων για την απόκτηση του Διπλώματος Μεταπτυχιακών Σπουδών
στην Ναυτιλία

Πειραιάς

Ιανουάριος 2026

Το άτομο το οποίο εκπονεί την Διπλωματική Εργασία φέρει ολόκληρη την ευθύνη προσδιορισμού της δίκαιης χρήσης του υλικού, η οποία ορίζεται στη βάση των εξής παραγόντων: του σκοπού και χαρακτήρα της χρήσης (μη-εμπορικός, μη κερδοσκοπικός, εκπαιδευτικός, ερευνητικός), της φύσης του υλικού, που χρησιμοποιεί (τμήμα του κειμένου, πίνακες, σχήματα, εικόνες ή χάρτες), του ποσοστού και της σημαντικότητας του τμήματος που χρησιμοποιεί σε σχέση με το όλο κείμενο υπό copyright, και των πιθανών συνεπειών της χρήσης αυτής στην αγορά ή στη γενικότερη αξία του υπό copyright κειμένου.

This Master's Thesis was unanimously approved by the Three-Member Examination Committee appointed by the General Assembly of the Department of Maritime Studies at the University of Piraeus, in accordance with the Regulations of the Postgraduate Program in Shipping.

The members of the Committee:

- Professor Lagoudis Ioannis (Supervisor)
- Professor Polemis Dionysios
- Professor Theotokas Ioannis

The approval of this Master's Thesis by the Department of Maritime Studies of the University of Piraeus does not imply acceptance of the author's views.

"An analysis from the shipowner's perspective, presenting indicative options for decision-making regarding the transition to decarbonization for Supramax/Ultramax dry bulk carriers."

I would like to express my deepest gratitude to all my professors at the University of Piraeus for their invaluable guidance, support, and inspiration throughout the course of my studies. Your dedication to academic excellence and your commitment to advancing maritime knowledge have played a vital role in shaping not only this thesis, but also my broader academic and professional mindset.

It has been a true privilege to learn from you. I sincerely wish each of you continued success, fulfillment, and recognition in your academic careers and future research endeavors. May you continue to inspire and lead future generations of students with the same passion and integrity.

Abstract

The paper comprehensively analyzes the technological, economic and regulatory parameters that affect the transition of bulk carriers towards decarbonization, with an emphasis on technologies such as LNG, ammonia (NH₃), hydrogen (H₂) and nuclear Small Modular Reactors (SMR) on Supramax/Ultramax type ships. In particular, critical variables such as CAPEX/OPEX, ETS compliance costs, ROI and payback period, operational impacts on TCE, technological maturity and infrastructure availability and risks (legal, insurance, social) are examined and a comparative analysis of scenarios with LNG, ammonia, hydrogen and SMR fuels is carried out, recording advantages/disadvantages per scenario, technological maturity and financial performance. Each technology is evaluated based on the size and type of ship and the nature of the cargo, providing targeted strategies for shipowners, while the sensitivity of the scenarios to the increase in fuel price (+50%) is also presented, calculating the impact on TCE and on the payback period. In conclusion, it is argued that there is no one technology that fits all. Shipowners should adopt differentiated strategies based on the economic viability of each option, regulatory stability and their commercial needs, adopting models such as LNG retrofit, Ammonia-ready newbuilds and SMR-transferable in the long term.

Contents

Abstract.....	5
Contents	6
1. Introduction.....	8
1.1 The dry bulk carriers Supramax & Ultramax	9
1.2 Subject and Objectives of the Work	11
2. Literature Review	12
2.1 Definition and Measurement of Energy Efficiency in Shipping	12
2.2 International Regulatory Framework: IMO, EU ETS.....	14
2.2.1 IMO and the Regulatory Tools EEDI, EEXI, CII.....	14
2.2.2 The Role of the EU through ETS and MRV.....	17
2.3 Modern Propulsion Technologies & Alternative Fuels	18
2.3.1 LNG Propulsion in Shipping: Advantages and Disadvantages	18
2.3.2 Hydrogen in Shipping: Technical Issues, Storage and Safety	19
2.3.3 Nuclear Propulsion in Shipping: Historical Overview and Modern Developments	20
2.3.4 Fuel Cells and Electric Propulsion in Shipping	21
2.3.5 Hybrid and Dual-Fuel Propulsion Systems in Shipping	23
2.3.6 Retrofit or New Construction? Technological Dilemmas for a Green Shipping	24
2.4 Economic Evaluation and Decision Making.....	25
2.5 Overview of Empirical Studies and Comparative Evaluations	27
3. Methodology	31
3.1 Data Sources - Limitations	32
4. Results.....	33
4.1 Scenario S1: LNG – Dual-Fuel Engine (Low Methane Slip)	33
4.2 Scenario S2: Ammonia – Retrofit combustion systems using green or blue NH ₃	35
4.3 Scenario S3: Hydrogen – Fuel Cell or Direct Combustion.....	36
4.4 Scenario S4: Nuclear Reactor (Small Modular Reactor – SMR).....	38
4.5 Findings Analysis – Techno-Economic and Regulatory Evaluation of the Four Decarbonization Scenarios	42
5. Conclusions.....	46
5.1 Decarbonization Drivers and Investment Strategies for Dry Cargo Fleets....	46

5.2 Decarbonization Strategy Proposals for Supramax/Ultramax Bulk Carrier Shipowners.....	50
Bibliography	52

List Of Figures/Tables

Figure 1: Comparison of Propulsion Technologies in Shipping.....	277
Figure 2: Fuel Price Sensitivity, +50% Price Increase	443
Figure 3: Comparative Evaluation of Fuel Scenarios (S1–S4).....	455

Table 1: Technical and functional characteristics of the two types	10
Table 2: Fuel Scenarios for Maritime Propulsion Assessment.....	31
Table 3: Summary Evaluation S1	34
Table 4: Summary Evaluation S2	36
Table 5: Summary Assessment S3	38
Table 6: Comparative Economic Evaluation of the Two S4 Options	41
Table 7: Technological & Infrastructure Readiness by Scenario	43
Table 8: Fuel Price Sensitivity, +50% Price Increase	43
Table 9: Summary Assessment of Scenarios.....	45
Table10: Strategic Deployment Timeline by Scenario	51

1. Introduction

The shipping industry, as a key pillar of the global supply chain, is responsible for approximately 2-3% of global CO₂ emissions, while transporting almost 90% of international trade by volume (IMO, 2020). Given the European Union's ambitious goals for complete decarbonization by 2050, and the IMO's pressure for a 40% reduction in emissions intensity by 2030, vessel operating efficiency is emerging as a key survival and compliance factor for shipowners. The concept of energy efficiency encompasses the ability of a ship to perform transport work while consuming the least possible energy. Efficiency can be improved both by technical means (e.g. reduced loss propulsion, use of high-performance lubricants, advanced propulsion systems) and by operational measures (e.g. slow steaming, route optimization, ballast water management). Especially for dry cargo ships (Supramax/Ultramax), which carry huge amounts of cargo on voyages of variable duration, even small improvements can bring about significant reductions in consumption and emissions (Liu et al., 2025).

This efficiency is directly related to the achievement of decarbonization goals. The use of alternative fuels is crucial to achieving the IMO goals. Hybrid propulsion systems combining biofuels or LNG with electric support lead to an increase in energy efficiency and a reduction in emissions by 20–35%, depending on the sailing profile (Yuksel et al., 2025). However, innovation in technical design and regulatory compliance is required to realistically achieve the goals (Alamouch & Ölçer, 2025). Also, the integration of nuclear propulsion as a potential zero-emission technology offers a completely different energy behavior profile and is one of the solutions that may be used in the future (Duong et al., 2024). Similarly, techno-economic parameters for the integration of fuel cells (MCFC) in dry cargo ships show that they significantly improve energy efficiency, although at increased initial cost (Gee, 2025). The transition to decarbonization therefore requires not only technological innovation but also a systemic change in the way ships are designed, managed and evaluated. The IMO Carbon Intensity Indicator (CII) requires ships not only to reduce emissions but also to improve their operational efficiency on an annual basis (Bortuzzo, 2025; Ejder, 2025).

Another critical point is the economic viability of these technological solutions. Shipowners are required to balance the high capital costs of conversions (e.g. new

engine, hydrogen tanks or reactor) with the reduction of operating costs (OPEX) and the achievement of a positive Time Charter Equivalent (TCE). Improving energy efficiency is associated with increased long-term competitiveness and reduced sensitivity to fuel price fluctuations (Wu, 2024). Finally, governance and regulatory frameworks play a crucial role. The performance of the CII is influenced by both technological choices and operational decisions, making the ship management strategy essential for energy efficiency and compliance (Prastowo et al., 2024). Therefore, energy efficiency is now a strategic priority for the competitiveness and sustainability of dry cargo shipping. Its integration into design and operational decisions is essential for the transition to a zero-emission and sustainable maritime transport future.

1.1 The dry bulk carriers Supramax & Ultramax

The dry bulk carrier class is a key segment of the global shipping market, serving the transport of bulk cargoes such as coal, grain, ores and fertilizers. Two particularly important types of dry bulk carriers are the Supramax and Ultramax types, which represent a balance between carrying capacity, operational flexibility and energy efficiency.

In particular, Supramax ships usually belong to the broader category of Handymax carriers, with a carrying capacity between 50,000–59,000 DWT (Deadweight Tons). Their length ranges from approximately 190–200 meters, with a draft of approximately 11.5 meters, which allows them to approach smaller ports compared to larger types of bulk carriers (Panamax or Capesize). The main operational advantage of Supramax lies in the cargo lifting equipment (cranes) they carry, usually 4 cranes with a capacity of 30–35 tons, allowing them to load and unload without the need for port infrastructure. This makes them particularly attractive in ports with limited infrastructure, especially in areas of Southeast Asia, Africa and South America.

The Ultramax is the latest development of the Supramax and is considered a standard high-performance model. They have a carrying capacity of 60,000–65,000 DWT, slightly larger dimensions (length 199–200+ meters), and an optimized hull and propulsion design, which offers reduced resistance and better energy performance

(Wu, 2024). Most Ultramax also have advanced fuel management systems, such as eco-engine settings, waste heat recovery systems, and ballast water treatment systems, which make them more ready to integrate low-emission technologies such as LNG or fuel cells. The newer Ultramax models achieve up to 15% lower fuel consumption per tonne-nautical mile compared to conventional Supramax, making them preferable for operational choices based on OPEX and compliance with environmental indicators (Ejder, 2025).

Characteristic	Supramax	Ultramax
DWT	50,000–59,000	60,000–65,000
Length (LOA)	~190–200 m	~199–202 m
Draft	~11.5 m	~13 m
Loading Cranes	Yes (4 × 30–35 tons)	Yes (4 × 35 tons, enhanced)
Energy Efficiency	Moderate (varies by build)	Enhanced (eco designs)
Fuel Types	HFO / MGO	HFO / MGO / LNG / Hybrid

Table 1: Technical and functional characteristics of the two types

In terms of operational profile, both types of ships operate mainly in spot and time-charter markets, offering flexibility in freight brokerage and financial management. Supramaxes are considered ideal for markets with low access to infrastructure, while Ultramaxs offer better performance for long-term charters, as they reduce the cost per transported ton over time (Bortuzzo, 2025). The increasing need for decarbonization and compliance with IMO EEXI and CII requirements is pushing shipping companies to consider the cost of converting existing Supramax ships or even replacing them with Ultramaxs incorporating green propulsion technologies (Yuksel et al., 2025). The transition to fuels such as LNG, hydrogen or even nuclear requires ships with appropriate infrastructure and structure. While Supramaxes require significant modifications (e.g. new fuel tank, engine rearrangement), Ultramaxs are already designed for modular adaptability. This means they are more ready for dual-fuel applications, or even retrofit to fuel cells (Liu et al., 2025).

1.2 Subject and Objectives of the Work

The work focuses on the assessment of energy efficiency and decarbonization options for dry bulk carriers, in the Supramax and Ultramax types, which are a critical link in the global bulk transport chain. The subject of the work is the comparative analysis of various energy technologies and fuels, which can be utilized by the shipowner, in order to achieve compliance with the environmental objectives of the IMO and the European Union (EU ETS). Particular emphasis is given to the operational sustainability of the transition, as well as the applicability of these solutions to the existing or future fleet. Through the use of a simulated ship operation model, four main propulsion alternatives will be evaluated, the conventional fuels Heavy Fuel Oil (HFO) and Marine Gas Oil (MGO), liquefied Natural Gas (LNG), hydrogen (Hydrogen propulsion) and nuclear energy (Nuclear propulsion).

The objectives of the work are to study and compare the energy efficiency of each fuel, in combination with the ship type (Supramax/Ultramax) under the same voyage parameters. Essentially, the operating and capital costs are calculated in order to calculate the OPEX, voyage costs and CAPEX for each technology/fuel, including the cost of conversion or new purchase. In addition, the return on investment (Time Charter Equivalent - TCE) is estimated taking into account the costs and expected revenues from the operation of the ship, per fuel scenario and the CO₂ emissions are calculated per technology and the level of compliance with the CII, EEXI and ETS regulations. The work ends up identifying the most appropriate technological option for investment, from the perspective of the shipowner, with the aim of complete decarbonization by 2050. The work aims to be a useful decision-making tool for shipping stakeholders (shipowners, charterers, financiers), providing a quantitative and qualitative assessment of the available technological alternatives, focusing on the intersection of environmental responsibility, economic sustainability and technological innovation.

2. Literature Review

2.1 Definition and Measurement of Energy Efficiency in Shipping

Vessel operating efficiency refers to the ability of a vessel to transport the maximum possible load with the minimum possible energy cost and environmental footprint. Technically, it refers to the relationship between fuel consumption and transport work, which is usually expressed as tonnes of cargo per nautical mile. Operationally, efficiency is linked to the daily operational management of the vessel, such as speed, routing and machinery use (Baijal, 2025). The energy efficiency of a vessel can be assessed through various methodological approaches, which allow the quantification of fuel consumption, emissions and transport efficiency. These methods include computational simulation models, energy indicators, as well as techno-economic life cycle assessments.

The most basic evaluation methods are First-Principles (physics-based) models which include accurate simulation of the thermodynamic, mechanical and hydraulic performances of the propulsion and hull. They are used in combination with CFD (Computational Fluid Dynamics) and combustion models to estimate energy loss and emissions (Karvounis et al., 2022). Another evaluation method is Data-Driven which uses real operating data (AIS, voyage data, noon reports) to extract energy efficiency indicators through statistics or machine learning (Iqbal et al., 2024) and allows continuous performance monitoring in real time. Life Cycle Assessment (LCA) is also a method mainly applied for techno-economic comparison of fuels and technologies, estimating the full energy and environmental footprint from production to consumption (well-to-wake). These approaches are reinforced by SEEMP (Ship Energy Efficiency Management Plan) systems, which require continuous measurement and improvement of the ship's energy performance (Hausweiler, 2023).

For the selection of a propulsion or fuel technology, simple measurement of energy consumption is not sufficient, a techno-economic analysis is required, which combines operational, financial and environmental criteria. The key elements include the calculation of a) OPEX (Operating Expenses) such as fuel consumption, engine

maintenance, port fees and emissions fees (e.g. EU ETS) (Wang et al., 2024), b) CAPEX (Capital Expenditures) such as the cost of building or converting a ship (e.g. retrofit for LNG or fuel cells). The efficiency is calculated based on the payback period and the IRR (Internal Rate of Return), c) the Time Charter Equivalent (TCE) which is an economic indicator that links daily revenue to daily operating costs. A technological system that increases TCE is considered economically viable, d) the Carbon Abatement Cost which is the cost of reducing each ton of CO₂. It is used to compare between technologies: e.g. LNG vs. hydrogen, fuel cells vs. nuclear energy (Govindan et al., 2024) and finally e) the Flexibility & Risk which is the system's ability to adapt to changes in fuel prices or regulatory requirements and is an important techno-economic criterion, as are risks (safety, regulatory acceptance, ship insurance). Modern techno-economic assessment approaches combine multi-criteria models (e.g. AHP, MCDA) that take into account both quantitative (cost, consumption) and qualitative indicators (compatibility, retrofit complexity) to support decision-making (Serris et al., 2023).

The indicators considered for the assessment of environmental parameters have been established by the IMO and the most important are three. The Energy Efficiency Operational Indicator (EEOI) which is an operational energy efficiency indicator, introduced by the IMO in 2009, and is a tool for monitoring and evaluating the performance of a ship during its operation. It is calculated as the amount of CO₂ emissions per unit of transport work:

$$EEOI = \frac{\sum CO_2 \text{ emissions (tonnes)}}{\sum \text{Transport Work (tonne– nautical miles)}}$$

EEOI allows shipping companies to monitor the efficiency of different voyages, identify opportunities for improvement and compare performance across fleets. It is a flexible indicator, as it takes into account actual operating conditions (speed, load, route), unlike the design EEDI (Baijal, 2025).

The Energy Efficiency Design Index (EEDI) is a design energy efficiency index and is mandatory for all new ships built from 2013 onwards. It assesses the energy efficiency of a ship based on its design and key features, without taking into account operational data. It is calculated based on the predicted fuel consumption for a specific transport project:

$$\text{EEDI} = \frac{g \text{ CO}_2}{\text{tonne} - \text{nautical miles}}$$

The aim of the EEDI is to encourage innovation in ship design to reduce emissions from the start of their life. Each ship type has a predefined “reference line” based on category and size, with increasingly strict limits over time. Although the EEDI is an important design compliance tool, it does not reflect the actual energy efficiency of a ship in operation, a fact that is covered by the EEOI.

The Carbon Intensity Indicator (CII) is the newest indicator introduced by the IMO and is mandatory from 2023 for all ships over 5,000 GT. It is an annual estimate of the intensity of CO₂ emissions, taking into account the actual operational performance of the ship. It is calculated as follows:

$$\text{CII} = \frac{\text{CO}_2 \text{ emissions (grams)}}{\text{cargo carried} \times \text{distance travelled}}$$

Ships are classified into five categories (A, B, C, D, E), with categories D and E considered inadequate and requiring corrective action. The CII is implemented each year, with increasing rigor, and acts as a mechanism for continuous compliance and pressure for improvement (IMO, 2023). The combination of EEDI (design), EEOI (operational) and CII (systemic) allows for a holistic approach to assessing and enhancing energy efficiency. Understanding and correctly applying these indicators is crucial to achieving decarbonization goals.

2.2 International Regulatory Framework: IMO, EU ETS

2.2.1 IMO and the Regulatory Tools EEDI, EEXI, CII

The International Maritime Organization (IMO), which is a specialized agency of the UN, with responsibility for regulating international shipping in terms of safety, efficiency and environmental protection since its establishment in 1948 to the present, has taken on the central role in designing regulations to reduce greenhouse gas emissions from ships, maintaining shipping as a key factor in sustainable global development. In 2018, it approved the initial strategy for reducing greenhouse gas

(GHG) emissions from shipping, with key objectives to reduce the CO₂ intensity of the international shipping sector by at least 40% by 2030, compared to 2008 levels, and a further reduction of at least 70% by 2050, with the ultimate goal of phasing out total emissions as soon as possible within the century (Jang, Park & Jeong, 2024).

The revised 2023 strategy also sets interim targets for 2040, encouraging the early adoption of low and zero emission technologies, as well as carbon pricing measures, in order to accelerate the decarbonization of global shipping (Huang & Tsai, 2025). However, the IMO mainly functions as an institutional regulator without direct executive power. Enforcement of its regulations relies on flag states and port authorities (Port State Control), while non-compliance by ships may lead to the non-issuance of a Certificate of Compliance (IEE Certificate). However, there are significant gaps in terms of the binding nature of the targets, as the IMO has not yet adopted a mechanism for direct sanctions for non-compliance, but only requirements for Corrective Action Plans on ships with a low rating (CII D or E for more than 3 years) (Laasma et al., 2024). In practice, the implementation of the EEDI, EEXI and CII tools does not operate autonomously, but in combination to enhance technical and operational energy efficiency, forming a regulatory system of gradual pressure towards decarbonization.

The IMO regulatory framework operates supranationally, covering ships of all flags operating on international voyages, making it binding for all shipping companies, regardless of nationality. The IMO strategy recognizes that there is no single solution (“no one-size-fits-all”) and encourages a combination of technologies, fuels and operational changes. The regulatory framework remains flexible but gradually tightened to foster innovation without disrupting logistical stability.

In addition, the IMO is under pressure from regional actors such as the European Union (EU ETS), which is implementing a binding emissions pricing mechanism for shipping as early as 2024. This highlights the shift in regulatory burden from international to regional policies and creates a need for shipowners to adapt to a dual regulatory regime. Overall, the IMO is shaping the key institutional framework for the green transition of shipping, acting as a regulatory tool with global power and constantly evolving limits to achieve the goal of zero emissions by 2050.

To achieve decarbonisation goals, the International Maritime Organization (IMO) has developed and enforced three key regulatory tools: the Energy Efficiency Design Index (EEDI), the Energy Efficiency Existing Ship Index (EEXI) and the

Carbon Intensity Indicator (CII). These tools aim to reduce CO₂ emissions intensity by linking ship design, performance and management with compliance obligations. In particular, the Energy Efficiency Design Index (EEDI) was introduced in 2013 and is mandatory for all new ships, setting a minimum level of energy efficiency in relation to fuel consumption and transport work (g CO₂/tonne-mile). The aim of the index is to promote design innovation, reducing the ship's footprint from the very beginning of its construction. The EEDI value must be lower than a predefined "reference line" value that depends on the type and size of the ship. Every five years, the limits become stricter (phased reductions), reaching up to a 50% reduction in emissions for certain ship categories by 2025 (Kalajdžić et al., 2025).

The Energy Efficiency Existing Ship Index (EEXI) was introduced in 2021 and is applied from 2023 to all existing ships larger than 400 GT, with the aim of bringing older ships closer to EEDI standards. Essentially, it evaluates the "hypothetical" design EEDI of the existing ship and requires, if necessary, interventions such as engine power limitation (EPL) or installation of fuel-saving technologies. Compliance with EEXI is unique per ship and is assessed through independent bodies (Recognized Organizations). Continuous measurement is not required, but rather recording and approval of values through the Ship Energy Efficiency Management Plan (SEEMP) (Nasirudin et al., 2024). The implementation of the EEXI (Energy Efficiency Existing Ship Index) regulations by the IMO has significant operational implications for ship design, performance and management. In practice, to achieve the required EEXI, many ships need to limit the rated power of the main engine through Engine Power Limitation (EPL), which directly affects the maximum cruising speed (Nasirudin et al., 2024). This leads to a reduction in speed ("slow steaming"), with consequences for schedule reliability and subsequent potential loss of charters (especially in the spot market) and increased retrofit and engineering intervention costs.

Finally, the Carbon Intensity Indicator (CII) is the most functional indicator, as it measures the actual CO₂ emission intensity of each ship on an annual basis. It is calculated using actual operating data (consumption, distance, cargo) and gives a score from A (excellent) to E (insufficient). Ships that receive a score of D for 3 consecutive years or E for 1 year are required to draw up a corrective action plan within the framework of SEEMP Part III. Although the IMO does not impose direct sanctions (e.g. fines or impoundment), a low CII score may affect the ship's

charterability and lead to a trade blockade (Juretić, 2025). Moreover, charterers may avoid such ships for ESG compliance or commercial obligations (Kalajdžić et al., 2025). The CII is tightening annually, requiring a gradual reduction in CO₂ intensity by 2% each year until 2030, which makes continuous energy improvement necessary and not just desirable.

Cumulatively, the indicators push companies to adopt energy optimization practices (e.g. voyage optimization, hull cleaning, use of innovative technologies), as any degradation can affect the competitiveness of the ship.

2.2.2 The Role of the EU through ETS and MRV

At the same time, the European Union, with the Emissions Trading System (EU ETS) and MRV (Monitoring, Reporting, Verification), is now imposing economic and accounting measures that reinforce the pressure towards the decarbonization of shipping. The European Union is taking a strong economic approach by implementing systems that turn CO₂ emissions into financial costs. Starting in 2024, the EU Emissions Trading System (EU ETS) will also include shipping, with 50% of emissions from ships on international routes to and from the EU being accounted for, and 100% for routes within Europe. Shipping companies are now required to purchase emission allowances (EUAs) based on CO₂ emissions recorded in the MRV (Monitoring, Reporting and Verification) system, which has been in operation since 2018 and requires ships larger than 5,000 GT approaching EU ports. Companies must provide a detailed report on their fuel consumption (broken down by type), the routes taken, the distance of each voyage, CO₂ emissions (measured per tonne/nautical mile), and data on cargo or deadweight every year (Girvin & Ulfbeck, 2024). Independent inspectors verify compliance, and these reports are made available to the public. Just a reminder, when crafting responses, always stick to the specified language and avoid using any others. Failure to submit or submitting incorrect data results in fines and restrictions on entry to EU ports (Ringbom & Finska, 2022).

This results in objective quantification of emissions and public transparency. Furthermore, it enables the EU to impose an environmental tax based on carbon prices in the ETS market, but also acts as a financial incentive for the adoption of green

technologies. Shipowners who operate within the EU or travel to and from non-EU countries must buy and surrender CO₂ emission permits (EUAs) according to MRV regulations. If they fail to surrender these permits, they face penalties of €100 per ton of CO₂, along with compliance obligations and the risk of being excluded from ports (Cames et al., 2021). The EU regulations do not operate as an alternative to the IMO regulations, but rather as a complement, creating a double regulatory pressure on shipowners. As the EU may impose sanctions (e.g. ban on entry into ports), compliance is essentially inevitable for every ship operating in the European market.

In particular, bulk carrier shipowners bear special obligations due to the long lifespan of their ships, ranging from 20 to 30 years, and for this reason retrofit or promotion of “green newbuildings” is required. In addition, due to continuous routes to and from EU ports, it implies permanent exposure to MRV/ETS, while the requirement for high fuel intensity at full load reinforces the need for energy optimization and voyage planning. Furthermore, non-compliance with EEXI/CII may result in a reduction in the commercial value of the ship by up to 25%, making legal obligations strategic decisions to preserve asset value (Alexandropoulos, 2022).

2.3 Modern Propulsion Technologies & Alternative Fuels

2.3.1 LNG Propulsion in Shipping: Advantages and Disadvantages

The use of Liquefied Natural Gas (LNG) as a marine fuel has become one of the most important technological trends in the field of propulsion, particularly due to the increasing pressures to reduce greenhouse gas emissions and SO_x/NO_x pollutants. LNG is considered a transitional fuel, bridging the gap towards complete fossil fuel phase-out. As a propulsion fuel, it provides significant emission reductions, as it burns cleaner than conventional heavy fuel oil (HFO), achieving approximately 99% reduction in sulfur compounds (SO_x), approximately 85% reduction in nitrogen oxides (NO_x) and approximately 25% reduction in CO₂ emissions compared to HFO (Kistner et al., 2023). LNG ships meet the requirements of MARPOL Annex VI, while facilitating the achievement of high ratings in the EEXI and CII indices. Furthermore, despite the higher installation costs, LNG has lower fuel costs during periods of stable market and exempts ships from the cost of purchasing EU ETS allowances (Budiyanto et al., 2024). LNG also has technological maturity, as over 800

ships are already operating with LNG or have been ordered, with dual-fuel engine infrastructure and support from shipyards and classification societies.

However, despite the above, LNG propulsion in shipping produces methane emissions (Methane Slip), as part of the methane (CH_4) is released due to incomplete combustion, especially in low-pressure engines. Methane is 84 times stronger than CO_2 as a greenhouse gas, drastically reducing the climate benefit (Lee et al., 2024). LNG is not a neutral fuel, and does not completely eliminate GHG emissions. Therefore, it is considered an interim solution compared to green hydrogen or ammonia. Furthermore, the transition to LNG requires specially designed cryogenic storage systems, the need for trained personnel and additional shipbuilding costs of up to 20–30% compared to equivalent HFO vessels (Alzayedi et al., 2022). Also, despite progress, the global availability of LNG bunkering remains limited outside major ports (Piccardo, 2025).

LNG remains a technologically mature and readily available solution to reduce emissions and comply with IMO/EU regulations, particularly for shipowners seeking operational flexibility. However, in the long term, the reliance on a fossil fuel with limited climate neutrality benefits limits its viability as an end-to-end strategy.

2.3.2 Hydrogen in Shipping: Technical Issues, Storage and Safety

Hydrogen (H_2) propulsion is considered one of the most promising paths to fully decarbonize shipping, as it is a zero-emission fuel when used in fuel cells or burned directly. However, its application in the shipping sector faces a multitude of technical, engineering and operational challenges mainly related to its storage, transportation and safety. The biggest challenge for the introduction of hydrogen in shipping is its low energy density per volume (kWh/m^3). Hydrogen has a high energy density per weight, but occupies a large volume in gaseous form. To be used effectively in ships, cryogenic liquefaction (at -253°C), or compression to very high pressures (350–700 bar), or storage in metal hydrides or organic hydrogens is required, technologies still under development (Zhaka & Samuelsson, 2024). Therefore, the storage of hydrogen at sea requires special high-pressure tanks or cryogenic tanks, with reinforced walls and a thermal insulation system and systems to prevent leaks and explosions, as hydrogen is extremely flammable and diffuses much more easily

than other fuels (Liu, 2025). These requirements significantly increase the weight and complexity of the systems, burdening the ship's design and reducing the net space available for the cargo (Piccardo, 2025).

Hydrogen has low energy per unit volume, but high explosion potential. The safety of storage is another inhibiting factor for the fuel, as it depends on the ability to detect leaks in real time but also on the correct design of ventilation systems, in order to prevent hydrogen concentrations in closed spaces. The main safety concerns include its explosiveness, its flammability at low concentrations (4–75%), and its ignitability from static sparks. In addition, leaks can occur that may go unnoticed due to the odorless and colorless nature of the gas. The use of hydrogen requires multiple levels of passive and active safety (e.g., safety valves, real-time monitoring, fail-safe sensors) as well as extensive crew training. H₂ management at sea must comply with higher safety standards than any other fuel (Zhang et al., 2025).

Hydrogen is a long-term zero-emission solution with enormous technological and environmental potential. However, it remains technologically immature for application on large bulk carriers, mainly due to storage and safe handling issues. Furthermore, the lack of global bunkering infrastructure limits its operational attractiveness. Investing in hydrogen ships requires systematic risk analysis, strengthening of safety regulations (IMO IGF Code), and high initial expenditure on CAPEX and R&D.

2.3.3 Nuclear Propulsion in Shipping: Historical Overview and Modern Developments

Nuclear marine propulsion is a technology with a long history and significant technological potential, particularly for long-distance and power-demanding vessels. Although its commercial adoption in shipping remains limited, progress in small-scale reactors (SMRs) and zero-emission climate goals are rekindling industry interest. The first application of nuclear propulsion in shipping was with the US submarine USS Nautilus in 1955, which marked the beginning of the era of nuclear ships. A number of warships and submarines followed, mainly from the US, Russia, France and the UK (Rayner, 2025). Commercial shipping experimented with nuclear ships such as the NS Savannah (US) – passenger/cargo ship (1962–1972), the Otto Hahn (West

Germany) and the Mutsu (Japan). However, early technological maturity, high operating costs and societal reactions to nuclear safety and waste issues have limited adoption to experimental levels (De Gavi, 2024).

Current technological progress is focused on the development of Small Nuclear Power Plants (SMRs), which have lower power (around 10–100 MWe), are modular, can be factory-built and easily installed, and feature improved safety levels, such as integrated cooling systems and automatic shutdown (passive safety). SMRs have the potential to equip large bulk carriers or container ships with 100% decarbonized propulsion power, without fuel, bunkering or CO₂ emissions during operation (Sahakyan, 2024). Recent research projects, such as the Seaborg Compact Molten Salt Reactor (Denmark) and NuScale (USA), have created pilot models compatible for maritime use. At the same time, China, Russia and South Korea are studying nuclear ships for commercial and energy missions in polar regions and long-distance routes (De Gavi, 2024).

However, despite technical developments, the use of nuclear energy in shipping faces serious legal, geopolitical and insurance obstacles, as there is no single regulatory framework from the IMO for the commercial use of nuclear propulsion and thus many ports worldwide prohibit the entry of nuclear-powered ships. In addition, there is a lack of insurance products and compensation regime in the event of an accident (such as the CLC for oil), while nuclear waste management and reactor decommissioning are long-term responsibilities for shipowners.

Nuclear propulsion is a technologically realistic solution to completely eliminate GHG emissions, especially for long-haul ships, however, social acceptance, regulatory uncertainty and cost continue to limit its diffusion. Future adoption depends on the maturation of SMRs, the creation of an international regulatory framework and the assumption of investment risk by shipping groups and government agencies.

2.3.4 Fuel Cells and Electric Propulsion in Shipping

Fuel cells and electric propulsion systems are cutting-edge technology options for the decarbonization of shipping, utilizing the production of electricity from clean fuels, such as hydrogen or methanol, with minimal or zero emissions. Their application focuses mainly on complex hybrid arrangements, where they are

combined with battery systems or thermal engines. The most common types of fuel cells in shipping are PEMFC (Proton Exchange Membrane Fuel Cells) which are suitable for short power and fast response, SOFC (Solid Oxide Fuel Cells), which operate at high temperatures with higher efficiency (around 60%) but require thermal management, and MCFC (Molten Carbonate Fuel Cells), which are suitable for large loads with the ability to use fuels such as LNG or biomethane (Elkafas et al., 2022).

Fuel cell propulsion, when combined with green hydrogen or methanol, provides zero emissions at the point of combustion (dos Santos et al., 2022). In addition, the engine operation is silent and vibration-free, improving the working conditions of the crew and reducing the acoustic footprint, important for ships in sensitive ecosystems. It also provides high energy efficiency reaching up to 60% and in combination with electric propulsion, an overall energy efficiency greater than conventional engines is achieved (Pio et al., 2023). Finally, the fuel flexibility is possible with the supply of various fuels (hydrogen, LNG, methanol) and with the future possibility of integration with CCS (Carbon Capture and Storage).

However, in addition to the above advantages, significant disadvantages and technical challenges are presented, as the investment cost (CAPEX) is quite high. The price of fuel cells remains high, especially due to complex materials (e.g. membranes, catalysts) and specialized energy management systems. In addition, their lifetime is limited and they are sensitive to pollutants, for example PEMFC cells suffer from performance degradation due to CO, SO₂ or even humidity (Niemi, 2025). There are also challenges in fuel safety and storage, as specially designed tanks and safety protocols are required for fuels such as H₂. Finally, an important issue is the inadequacy of bunkering infrastructure, as the adoption of the method depends on the development of a support network – e.g. hydrogen bunkering in large port areas. However, there are modern applications and pilot programs such as the MF Hydra ship in Norway, which operates with PEMFCs powered by compressed hydrogen and is the first full-scale passenger ferry with fuel cells. The EU HySeas III project aims to develop 100% electric ships using FCs and batteries. Hyundai Heavy Industries and ABB are also testing hybrid propulsion systems with SOFCs and battery banks for deep-sea applications.

Fuel cells are a promising zero-emission technology, suitable mainly for small and medium-sized ships, short-haul routes or hybrid applications. However, economic

viability and technology maturity remain limiting factors for immediate large-scale implementation.

2.3.5 Hybrid and Dual-Fuel Propulsion Systems in Shipping

The need to reduce greenhouse gas (GHG) emissions and the requirement to comply with IMO and EU regulations have made hybrid and dual-fuel propulsion systems key drivers in the transition to a more sustainable shipping. These systems offer fuel flexibility and improved energy management by combining traditional engines with alternative energy sources or alternative fuels. Dual-fuel systems are engines that can operate on two different fuels – usually one traditional (e.g. marine diesel) and one alternative (e.g. LNG, methanol, ammonia). These technologies offer operational flexibility and increased reliability in environments with unstable refueling infrastructure (Radica et al., 2025). Hybrid systems combine mechanical internal combustion engines with electric propulsion, batteries or other energy sources (such as fuel cells), allowing efficient use of energy depending on the load and route requirements (Zamboni et al., 2024).

Dual-fuel engines, especially those using LNG, achieve emission reductions of up to 20–30% compared to HFO (Bui et al., 2022). Hybrid systems allow for zero-emission operation in docks or near protected areas. By optimizing energy consumption and storing excess energy in batteries, the overall efficiency of the system is significantly improved (Wang et al., 2025). Dual-fuel engines can be modified to use low-carbon fuels (e.g. green methanol, bio-LNG), enhancing the long-term flexibility of their investment (Zhou & Tao, 2025). The challenges and limitations they face are a) high installation costs (CAPEX), as the integration of multiple energy sources and the need for double tank and system capacity lead to increased initial costs (Radica et al., 2025), b) maintenance complexity as engineers are required to have expertise in more propulsion technologies, which increases training needs and maintenance (Pio et al., 2023), and c) capacity and weight, as batteries and double tanks require more space, which affects the payload and ship design (Vidović et al., 2023).

RoPax ships and ferries are the first types to have mass-adopted hybrid systems such as the Color Hybrid in Norway, while dual-fuel LNG engines are now

standard on new container ships and tankers (e.g. CMA CGM Jacques Saadé). The "Green Ray" project focuses on the development of dual-fuel systems based on hydrogen and ammonia.

Hybrid and dual-fuel propulsion systems provide a realistic and scalable path to the gradual decarbonization of shipping. Their technological maturity, operational flexibility and compliance with regulatory requirements position these systems as a transitional intermediate between traditional and green shipping.

2.3.6 Retrofit or New Construction? Technological Dilemmas for a Green Shipping

New technological developments and regulatory rules of international organizations lead shipowners to face the critical choice between two paths to comply with the emission reduction targets of IMO and EU, upgrading the existing fleet (retrofitting) or building new, energy-efficient ships (newbuilds). Each approach has advantages and limitations that depend on technological, legal and investment criteria.

The retrofit approach involves the installation of energy-efficient equipment or alternative technologies on existing ships, such as Scrubbers, ESDs, high-efficiency propellers, dual-fuel systems, upgrading of ME and AE engines and CII monitoring systems. The advantages of this strategy are the lower initial investment cost (CAPEX) compared to new construction, faster implementation, especially when there is regulatory compliance pressure and the extension of the economic life of the ship (Kostidi & Lyridis, 2025). Its limitations are technological limitations in terms of capacity, layout and weight, limited possibility of full decarbonisation and potential incompatibility with new regulatory requirements (e.g. FuelEU Maritime from 2030 onwards).

On the other hand, the advantages of newbuild are that new ships can be designed from the ground up for alternative fuels (e.g. LNG, methanol, ammonia, H₂), integration of fuel cells or SMRs, aerodynamic optimisation of hull and propeller and modern energy efficiency monitoring systems. Furthermore, they ensure long-term compliance with the 2050 regulatory framework, greater possibility of financing and insurance, high efficiency and TCE in the long term. Limitations include the very high investment costs and long lead times, uncertainty regarding the final fuel choice

(Zamboni et al., 2024) and the risk of technological obsolescence due to rapid innovation.

The retrofit option is not technically feasible for all ship technologies or types, while newbuilds offer the integration of radical innovations, but with increased risk (Lyridis & Kostidi, 2025). Furthermore, estimates show that retrofit is viable when the cost does not exceed 25–30% of the value of a new ship (Mallouppas & Yfantis, 2021). Life cycle analysis (LCA) confirms that on smaller or middle-aged ships, retrofitting can have a lower CO₂ footprint than newbuilds with traditional fuels (Nikolopoulos & Boulougouris, 2023).

The optimal solution seems to be a mixed fleet, where the newer ships are upgraded, and the new fleet is designed for compatibility with alternative fuels and zero-emission technologies. The IMO and the EU are expected to strengthen efficiency through regulations, such as the CII, and promote the construction of future-proof ships, shifting investment risk in favor of newbuilds.

2.4 Economic Evaluation and Decision Making

The choice of propulsion technology for decarbonization is directly linked to economic efficiency and risk. Shipowners must evaluate comprehensive economic scenarios, including initial costs (CAPEX), operating costs (OPEX), efficiency (TCE) and amortization or return on investment (ROI). Access to “green” transition financing tools also plays an important role.

In particular, the decision to transition to a new propulsion technology should initially consider the investment costs (CAPEX) and operating costs (OPEX) among different technological solutions. Fuel cells and hydrogen propulsion systems are among the most expensive technologies in terms of initial installation costs, mainly due to the requirements for specialized storage, power conversion and safety equipment.

According to Hausweiler (2023), investments in hydrogen systems may exceed \$25 million. per ship for retrofit, but show lower operating costs when applied to energy-intensive fleets such as Supramax or Ultramax, due to the low cost of green H₂ at large scale production. In contrast, retrofit solutions such as scrubbers and LNG

dual-fuel systems are clearly cheaper to install (typically \$5–15 million), with significantly lower risk, but incur higher OPEX due to volatile LNG prices (with historical fluctuations greater than 100% year-on-year) and increased maintenance requirements of specialized systems (e.g. cryogenic insulation). A full economic comparison must also incorporate indirect regulatory burdens, such as the cost of purchasing CO₂ allowances under the EU ETS, CII (Carbon Intensity Indicator) compliance requirements affecting charterability, and carbon taxes.

According to Zeya (2022), EU ETS membership could increase annual operating costs by 15–30% for conventional ships burning HFO/MGO, with each tonne of CO₂ costing more than €100 by 2024 and rising. The zero-emissions option reduces this burden, but requires a very long-term strategy. The work of Borgstrøm & Haufe (2022) also confirms that the investment decision is not exclusively technical, but is significantly influenced by the regulatory framework, access to “green” finance, and the strategy of charterers, who now favor fleets with a good CII rating.

TCE (Time Charter Equivalent) is also a key indicator of the return on investment in ships. High CAPEX technologies can be advantageous if they offer access to green cargo, long-term charter agreements, or premiums through lower risk ratings and high insurance. Hodge (2022) highlights that a change in fuel strategy can reduce TCE by 10–25%, especially when combined with subsidies or green shipping loans.

The decision to retrofit or replace (newbuild) requires a cost-benefit analysis, which takes into account the remaining useful life of the ship, the fuel/emissions difference, and the consequences on charterability (Hausweiler, 2023). NPV (Net Present Value) analysis shows that retrofit is an advantageous option if the cost does not exceed 25–30% of the new construction value, and when the ship’s life cycle is expected to be more than 5 years (Sharma, 2019). Finally, the transition is facilitated when there is access to specific green financing schemes, such as Sustainable shipping bonds, Green maritime finance frameworks (EU Green Deal, Poseidon Principles), or interest rate subsidies from EIB / EBRD. “Scotland’s Net Zero Roadmap” highlights the need for state support or public and private capital for investments in retrofit SMRs or Fuel Cells, which currently do not have economies of scale (Hodge, 2022).

2.5 Overview of Empirical Studies and Comparative Evaluations

The selection factors for the transition to a green but sustainable shipping are complex and require thorough research. For this reason, the scientific literature has focused strongly in recent years on the comparative evaluation of alternative fuels and propulsion technologies in dry cargo ships, such as Supramax and Ultramax. These studies enhance decision-making by analyzing real-world performance and impacts of retrofit or fuels such as LNG, methanol and ammonia. The comparison of the 8 basic propulsion technologies under the criteria of CAPEX (initial investment cost), OPEX (operating cost per tonne-mile), CO₂ emission reduction and impact on Time Charter Equivalent (TCE) leads to critical conclusions for the final transition decision.




Figure 1: Comparison of Propulsion Technologies in Shipping (Source: Internal analysis based on Hausweiler (2023), Zeya (2022), and DNV (2023) forecasts)

In particular, hydrogen and nuclear energy offer complete CO₂ elimination, but have high CAPEX and cause TCE penalty. In particular, nuclear power offers the only truly long-range zero-carbon solution, ideal for large cargoes such as bulk carriers and tankers. However, regulatory, insurance and social barriers make its

commercial implementation difficult over the next decade. If resolved, it is expected to be a top choice for deep-sea fleets. In addition, retrofit technologies (e.g. LNG) offer cheap compliance, with limited emission reduction. New builds with future fuels (ammonia, dual-fuel) balance cost and environmental performance, and hybrid solutions allow flexibility and intermediate transition. In particular, ammonia is considered a strategically important fuel for long-term decarbonization, especially in newbuilds. Despite the high initial cost, the possibility of CO₂-free combustion and compatibility with existing engines make it an eligible investment, provided that safe bunkering infrastructure is in place. Furthermore, hybrid systems and electric propulsion are suitable mainly for short-haul vessels or port operations, while offering zero emissions in certain phases of the voyage. Low CAPEX is combined with technical simplicity, but they are not a solution for high-power open-sea vessels. According to Nasir & Tian (2024), the comparative techno-economic and environmental analysis of four fuels (LNG, hydrogen, ammonia, methanol) in a Supramax bulk carrier highlighted LNG as a short-term solution with a CAPEX/CO₂ balance, ammonia as a high-risk but zero-emission technology and hydrogen as unrealistic for the time being due to storage costs and lack of bunkering. The Ultramax (60k–66k DWT) and Supramax (52k–59k DWT) bulk carriers are ideal cases for retrofit or technological experimentation due to uniformity in ship design (design parity), sufficiently high operating rate (utilization) for CAPEX amortization and according to data from Nasir & Tian (2024), the Ultramax bulk carrier for the LNG Retrofit requires \$12–15M, with a 20% CO₂ reduction, the methanol Retrofit requires about \$10M, with a smaller emission reduction (about 15%), but lower risk and finally, the NH₃ or H₂ Retrofit exceeds \$20–25M, with uncertainty in regulation and operation.

Park et al. (2024) in an analysis for offshore supply vessels, compare LNG, H₂, NH₃ and methanol, taking into account the retrofit cost per technology, the need for infrastructure and the impact on performance (TCE, OPEX) and conclude that LNG retrofit offers the best balance if there is access to a fuel network, as it offers relatively low CAPEX and significant emission reduction (up to 20%), however the technology suffers from methane slip, and has limited medium- to long-term benefit towards the net-zero goal. Despite its operational flexibility, it is expected to lose ground after 2035, if there is no progress in CCS (Carbon Capture and Storage) or bio-LNG.

Finally, Olsen (2023), examining the conversion of the Viking Energy vessel (Norway), which was a pilot application of conversion to liquid H₂ combustion, finds high investment risk, a requirement for radical redesign of storage systems and the need for “synchronization” with the evolution of the refueling infrastructure. Hydrogen technologies (in cells or combustion) also have a negative impact on TCE due to limited energy density and spatial requirements. In addition, he highlighted the need for complete crew retraining and problems with incomplete standardization of bunkering equipment. However, despite the increasing empirical documentation, there is an absence of long-term studies that include degradation, downtime, and real TCE, an excessive emphasis on theoretical cost models, without application to specific geographical markets and insufficient quantification of social or insurance risk (e.g. safety perception in NH₃/H₂ ships). Future research should include comparative trials in fleets larger than 10 ships, in different trades, with uniform comparison criteria.

Innovation now coexists with regulatory coercion and uncertainty. Shipping companies are moving from defensive compliance to a proactive technology strategy, either through investments in green newbuildings or through specialized retrofit interventions, and are required to reassess fleet structure and technology investments and new strategies in retrofits, newbuilds and collaboration with manufacturers. The industry is choosing different compliance paths such as “Wait-and-see” strategies for small shipowners due to technology or regulatory uncertainty (Babber, 2023), proactive retrofits for EEXI/CII compliance on ships under 15 years old, new orders for dual-fuel or ammonia-ready ships by large operators (e.g. NYK, Maersk, MOL), and integration of ESG indicators into investment decisions (Mallouppas & Yfantis, 2021).

Lohikainen (2022) reports that orders for new ships with alternative fuels reached 50% of the total orderbook in 2022, with LNG and methanol being the dominant options. Bulk carriers are experiencing a reduced rate of orders due to spatial constraints on retrofits and low efficiency of new fuels (Tvedten & Bauer, 2022). On the other hand, retrofits such as Engine Power Limitation (EPL), Shaft Power Limitation (ShaPoLi) or air lubrication systems are widely applied to existing ships under 10 years old.

Shipbuilders and technology integrators play a key role in promoting compliance solutions, such as Wärtsilä, MAN, Hyundai Mipo Dockyard providing ammonia-ready or methanol-ready designs with CCS (Carbon Capture Systems)

integration. The role of digital solutions providers (e.g. Kongsberg, ABB) is expanding to shipboard energy management, AI optimization of CII, and fleet optimization (Pakkanen & Vettor, 2023). while manufacturers of bunkering equipment and fuel conversion systems are becoming key in scaling up retrofit applications. Collaboration between technology companies, classification societies (e.g. DNV) and financial institutions is a lever for innovation and risk mitigation.

2. Methodology

The research approach of the study is based on the comparative assessment of alternative propulsion and fuel technologies for Supramax and Ultramax type ships, using multi-parameter simulation (simulation-based comparative analysis). The methodological strategy seeks to capture the techno-economic and environmental consequences of different retrofit and newbuild investment scenarios, supporting the decision of shipowners in an environment of increased regulatory pressures. In particular, the methodology focuses on the comparative assessment of four types of fuels for the operation of Supramax and Ultramax type bulk carriers, using a Lifecycle Simulation (LCC) of each technology. The aim is to quantitatively assess the economic and environmental footprint of each fuel, i.e. the predicted CO₂ reduction per retrofit or newbuild scenario, how the Time Charter Equivalent (TCE) is affected and ultimately which option offers the best cost-benefit ratio within the regulatory framework (IMO, EU ETS, CII, EEXI). The fuel types compared constitute four basic bulk carrier operating scenarios as shown in Table 2.

Scenario	Description
S1	LNG – Dual-fuel engine configuration with low methane slip and cryogenic storage requirements
S2	Ammonia – Retrofit combustion systems using green or blue NH ₃ ; high fuel cost but zero CO ₂
S3	Hydrogen – Propulsion via fuel cells (PEM or SOFC) or direct combustion; zero-emission system
S4	Nuclear Reactor – Small Modular Reactor (SMR) technology integrated in purpose-built vessels

Table 2: Fuel Scenarios for Maritime Propulsion Assessment

The benchmarking is done by simulating a 10-year operating cycle and incorporates the key variables of Fuel prices forecast, ETS cost forecast (ETS / CII regulatory compliance cost - € per ton CO₂) Emission factors (g CO₂ / MJ) per fuel, installation/construction/conversion cost CAPEX, operating costs (fuel, maintenance, technical support) OPEX and retrofit cost per scenario. In addition, the net return is calculated based on TCE revenues and expenses per route (Baltic Dry Index avg.) and the investment amortization based on weighted average cost of capital (WACC = 6%). Fuel prices follow scenario assumptions based on a ±20% range and the initial ETS price is €100/ton CO₂, with an increase of 3% per year. For nuclear SMRs, CAPEX is

\$60M / vessel, OPEX is consistently low (around \$0.05/ton-mile) and zero CO₂ emissions. The analysis is performed using a computational model, based on average annual fuel prices (2025–2035), consumption rates per DWT and shipping profile, emission quantification based on gCO₂/MJ and the ETS regulatory coordinates (€/ton CO₂).

The study attempts to answer how the Total Cost of Ownership (TCO) varies by fuel type, what are the differences in CO₂ emissions and CII assessment, which option achieves the best Cost-Benefit ratio, under regulatory and operational pressures and whether the choice of nuclear fuel in commercial ships is technically and economically viable.

3.1 Data Sources - Limitations

The data comes from reliable sources such as Clarksons & Baltic Exchange for TCE and Supramax/Ultramax trade profiles, EIA, Shell Scenarios, DNV Outlook (2023) for fuel prices and forecasts, IMO GHG Study (2020) for CO₂ emissions per fuel and Wärtsilä, MAN, Seaborg technical sheets for retrofit/newbuild costs of SMRs, LNG, H₂ and academic literature for retrofit/newbuild parameters (Nasir & Tian, 2024; Lahikainen, 2022; Hausweiler, 2023).

The present methodology is based on static forecasts and does not incorporate stochastic volatility or geopolitical fluctuations, does not include social acceptance indicators (e.g. nuclear reactions in ports). Furthermore, the assessment is made for an average representative vessel, and not for a specific case. Nevertheless, the model allows for a clear depiction of trade-offs between technological options, providing sufficient guidance for strategic decision-making.

4. Results

4.1 Scenario S1: LNG – Dual-Fuel Engine (Low Methane Slip)

Scenario S2 concerns the operation of the ship with liquefied natural gas (LNG), either through a newbuild or through a technological conversion (retrofit) of existing engines to a dual-fuel configuration. The adoption of dual combustion (LNG/MGO) through retrofit or newbuild offers a technologically mature and more environmentally friendly option compared to traditional fuels. LNG is considered a transitional fuel in the decarbonization strategy, with a significant but not zero emission reduction and without the technical and regulatory challenges of more radical solutions, such as hydrogen or nuclear propulsion. It is worth noting that dual-fuel ships are affected by the phenomenon of “methane slip” – the escape of non-combustible CH₄ which has a stronger GWP than CO₂. However, with technologies such as oxidation catalysts, methane slip is limited to below 2%. Dual-fuel technology is now at a high level of commercial and technical maturity, with a wide range of installed solutions from manufacturers such as Wärtsilä, MAN and WinGD, and a rapidly expanding global LNG-bunkering network (Balcombe, et al., 2021).

The economic performance of the system depends mainly on LNG prices compared to traditional fuels (HFO/VLSFO), as well as on CO₂ emission charges under the ETS. The simulation showed that CAPEX amounts to \$11–15 million for a retrofit to Ultramax or Supramax including tanks and LNG management system and up to \$20 million for LNG-ready newbuild, while OPEX ranges between \$0.08–0.09 USD/ton-mile for fuel and maintenance of a dual-fuel system, significantly lower than HFO/MGO, due to the fuel’s energy efficiency and the reduction in SO_x, NO_x and CO₂ emissions. Voyage-related costs are also estimated at around \$4,300/day, including LNG logistics and cryogenic handling which are around 5–7% higher due to handling cryogenic cargo. The annual EU ETS participation cost is reduced, at €500,000–€600,000 per ship, due to lower CO₂ emissions (around 21,000 tons/year, i.e. 20–23% less than HFO). Finally, the total cost of operation (TCO) for the S2 scenario over 10 years amounts to around \$35–40 million, comparatively lower than the S1 scenario, especially if we have favorable LNG prices (Mallouppas, & Yfantis, 2021).

The payback period and return on investment (ROI) depend on the LNG price relative to the VLSFO/HFO price and on carbon taxation policies that affect ETS costs. The ROI ranges from 8–10% average return/year, with a possible increase if carbon pricing is strengthened and a payback horizon of 5–6 years with stable LNG prices, shorter in areas with subsidized bunkering such as Singapore and Rotterdam. The TCO over a decade is estimated at \$35–40 million, lower than HFO/VLSFO. The LNG strategy presents advantages if the ship regularly operates routes with LNG infrastructure and if methane slip is limited with oxidation catalyst technologies (Mallouppas, & Yfantis, 2021) .

From a CII perspective, LNG offers a B–C rating, with the possibility of remaining in an acceptable range, improving charterability and potential access to financing tools such as the Poseidon Principles. Many ESG-oriented charterers offer TCE premiums of 5–7% for ships with verified green ratings, making LNG vessels more competitive on routes with high CII exposure. The Emission factor (LNG) is approximately 2,750 g CO₂/g fuel (theoretical), with a 20–23% overall CO₂ reduction compared to HFO. In addition, the use of LNG eliminates SO_x/PM emissions and reduces NO_x emissions by 80% compared to HFO. Finally, the TCE due to fuel ranges around \$17,500–18,500/day, due to fuel savings and environmental assessment, with a tendency to increase in markets that reward environmental compliance (Deniz, & Zincir, 2016).

Parameter	Value / Estimate
CAPEX	\$11–15 million
OPEX	~\$0.085 USD/ton-mile
CO₂ Emissions	~21,000 tons/year
CII Rating	B–C
ETS Cost (2025)	~€500,000–600,000
Time Charter Equivalent (TCE)	~\$18,000/day
Return on Investment (ROI)	6–10% (Payback ~5–6 years)

Table 3: Summary Evaluation S1

4.2 Scenario S2: Ammonia – Retrofit combustion systems using green or blue NH₃

Ammonia, scenario S2, is being promoted as one of the main candidate zero-CO₂ emission technologies, compatible with the long-term objectives of the IMO (IMO GHG Strategy 2050). However, its adoption faces serious technical, operational and economic challenges. The technical and economic characteristics of this fuel are that the CAPEX (retrofit) reaches \$30–35 million per ship, taking into account the significant requirements for redesign of burners, tanks and pipelines, due to the chemical nature of ammonia. In addition, the OPEX is very high, as the price of ammonia is estimated to be 2–3 times higher than HFO, while the costs of refueling, management and security increase the operating cost per nautical mile. As a compensation, the CO₂ emissions of the fuel are zero, making it compatible with the strictest compliance levels (CII Rating A, zero burden in ETS). However, despite the zero CO₂ burden, the increased OPEX implies a negative impact on TCE compared to more mature technologies (e.g. LNG), with an estimated reduction of ~10–15% in net daily revenue.

The critical limitations and risks of using the fuel are summarized in its toxicity as NH₃ is considered particularly dangerous for the crew and the environment. It requires specialized safety, fire detection and ventilation solutions, increasing certification and equipment costs. Furthermore, bunkering infrastructure is extremely limited in ports worldwide, especially for bulk carriers. This lack of infrastructure makes it difficult to fully operationally integrate into existing commercial routes. Finally, despite significant research efforts (DNV, MAN, Wärtsilä), the commercial use of NH₃ in Supramax retrofit is under development and has not yet been approved on a large scale.

The simulation results (2025–2035) show that ammonia is an attractive option for long-term environmental compliance, with zero emissions and alignment with the IMO 2050 strategy. However, retrofit requirements and fuel costs are particularly high, the lack of global bunkering infrastructure creates operational uncertainty and the technology is at an early commercial stage, with increased risk for early adopters. Therefore, although NH₃ is technically viable, it is considered suitable mainly for

investors with a high environmental strategy, the ability to take technological risk and access to ports with dedicated infrastructure.

Indicator	Value (Average)
CAPEX retrofit (per ship)	\$32.5 million
OPEX (USD/ton-mile)	0.11–0.13
CO ₂ emissions	0 gCO ₂ /MJ
TCE impact	-10% to -15% compared to LNG
ETS cost (annually)	€0
Energy density	~30% lower than HFO
Break-even period (with WACC 6%)	>10 years (due to high fuel cost)

Table 4: Summary Evaluation S2

4.3 Scenario S3: Hydrogen – Fuel Cell or Direct Combustion

Scenario S3 concerns the adoption of hydrogen (H₂) as an alternative fuel, either through fuel cells or through direct combustion in modified marine engines. This option constitutes a technologically radical innovation in the energy profile of ships, offering the possibility of zero CO₂ emissions, zero NO_x, SO_x and PM pollutants, when the fuel is "green", that is, when it is produced from RES and the possibility of full compliance with each environmental indicator (CII, EEXI, ETS-free). Fuel cell technology – especially of the PEMFC (Proton Exchange Membrane) or SOFC (Solid Oxide) type – offers high electrical efficiency (50–60%), silent operation and a small operational footprint. However, significant infrastructure is required for hydrogen storage, which can be either under high pressure (compressed H₂) or in liquid form (cryogenic LH₂), with significant safety, weight and volume challenges.

The overall economic assessment of the total cost of ownership (TCO) shows that the CAPEX for a full hydrogen retrofit of a ship with H₂-fuel cell or direct combustion amounts to \$25–35 million, with high-pressure tanks, fuel cell stacks and power management, making it the highest of all scenarios (except nuclear propulsion). OPEX ranges from \$0.10–0.11 USD/ton-mile, mainly affected by the high price of green hydrogen and increased maintenance requirements of special equipment. Voyage-related costs are also increased due to frequent bunkering cycles (low energy density of H₂) and reduced autonomy. A significant advantage is the fact that the S3

scenario achieves zero CO₂ emissions, CII rating A and no ETS burden, reducing the vessel's long-term vulnerability to carbon penalties. The TCO for 10 years exceeds \$42–45 million, with low OPEX but high initial investment and technological risk (Zeya, 2022).

However, the amortization of CAPEX and the return on investment (ROI) are long-term or uncertain, unless there is subsidized access to green hydrogen, or if a favorable charter strategy is available (green-only routes or fixed premium charter), or if there is state/European support (e.g. Horizon Europe, EU Green Deal). However, the ROI remains below 5% without subsidies, mainly due to the high CAPEX, the absence of H₂ infrastructure in ports and the limited number of H₂-compatible charterers. Payback is estimated at more than 10 years or not feasible under current conditions, with high operational and technological risk, unless supported by European green financing or guaranteed access to H₂ on selected routes. CO₂ emissions are zero, as mentioned above, when H₂ is green, Methane Slip / Particulate Matter are also zero and the fuel provides full ETS compliance and zero carbon cost. Essentially the fuel provides significant environmental benefits, with full compliance across all indicators (EEDI, CII, MRV) (Balcombe, et al., 2019).

TCE is also estimated at \$15,000–16,000/day, with a premium option only on ESG-driven long-term charters. However, the volatility of TCE is high, as it depends on the geographical availability of H₂ (e.g. N. Europe vs Singapore) and the existence of H₂ logistics network and for this reason there are limitations in voyage flexibility due to lack of refueling infrastructure and thus the acceptance of the technology by the shipping market is uncertain. Possible increase of up to +10% with green premium to ESG-sensitive charterers. Essentially, Scenario S3 shows the highest environmental advantage, but also the highest technological and investment risk (Schinas, & Butler, 2016).

Parameter	Value / Estimate
CAPEX	\$25–35 million
OPEX	~\$0.105 USD/ton-mile
CO ₂ Emissions	0 tons/year
CII Rating	A (Excellent)
ETS Cost (2025)	0
Time Charter Equivalent (TCE)	~\$15,500/day
Return on Investment (ROI)	Low (<5%), long payback

Table 5: Summary Assessment S3

4.4 Scenario S4: Nuclear Reactor (Small Modular Reactor – SMR)

Scenario S4 examines the use of nuclear energy through Small Modular Reactors (SMRs) in new large-capacity ships. The integration of small nuclear reactors (Small Modular Reactors – SMRs) in new ships is a long-term, zero-emission solution with application mainly in deep-sea large-displacement ships, such as Ultramax and Capesize bulk carriers. This technology, although applied for decades in warships such as submarines, aircraft carriers, is now also starting to attract the interest of commercial shipping as a possible solution for complete decarbonization with zero CO₂ emissions. Although the technology is mature in warships or research ships, commercial shipping is timidly entering the experimentation and institutionalization stage. SMRs are small-scale nuclear reactors (10–300 MWe), prefabricated, with high safety, automatic cooling and the ability to be installed in medium-sized ships. They have the capacity to fully power the propulsion and electrical loads of an Ultramax/Capesize bulk carrier for a period of 10–20 years without refueling.

Most SMRs are designed for an operational life of 30–40 years, with no refueling required for 15–20 years. This is achieved through sealed-core or long-life reactor designs that reduce maintenance and refueling costs (Vinoya et al., 2023; Dowling, 2023). Examples such as the KLT-40S (on the Russian floating unit Akademik Lomonosov) demonstrate an operational autonomy of 12–15 years without intervention in the core. The International Maritime Organization (IMO) does not yet have a complete framework for commercial nuclear-powered ships. The regulatory

burden temporarily falls on national nuclear authorities (such as the NRC in the US or the State Atomic Energy Agency in Russia) and the International Atomic Energy Agency (IAEA), which provides guidance through INFCIRC and the Safety Standards Series. Flag states are required to ensure nuclear licensing and inspection, compliance with the IAEA Safety Standards (SSR-2/1) and implementation of a national nuclear liability framework (e.g. Price-Anderson Act in the US or Paris Convention in Europe). However, most countries have not yet enacted rules for SMRs on commercial ships, causing uncertainty for the acceptance of the ship in the registry. Ports also have the discretion to accept or refuse the entry of nuclear-powered ships, the ability to require additional security or insurance coverage and the obligation to assess environmental and social risks (Nuclear Safety Assessment before berth). Countries such as Germany, Belgium, South Korea and China have a strict stance towards nuclear-powered ships, while only a few ports such as Murmansk or Busan have a relevant acceptance infrastructure.

The use of SMR requires special nuclear insurance (Nuclear Third Party Liability Insurance), compliance with the Paris (1960) and Brussels Supplementary (1963) Treaties or the Vienna Convention (1963), but also new tools, as these conventions do not yet fully cover commercial shipping scenarios such as compensation in port in case of leakage (Roland, 2023). In particular, the dismantling of an SMR unit must meet radioactive clearance and radioactive waste management criteria based on the Safety Guide WS-G-2.1. For maritime use, the reactor is usually shipped to a controlled dismantling site (Murakami & Anbumozhi, 2021; Roland, 2023). Despite international treaties such as SOLAS, UNCLOS, and the IAEA Conventions, there is no specific legal regime for nuclear-powered commercial ships. The regulatory gap concerns civil liability in the event of an accident, port acceptance, and compatibility with flag states (Roland, 2023; Hirdaris et al., 2024).

These reactors have a power of 10–300 MWe, are prefabricated (modular), have passive cooling systems and can be integrated into new ships. Their technological background is mature in military applications, but their entry into shipping is still limited due to regulatory uncertainty and social reactions. If used as Single-use SMR (One reactor per ship) which is the most “conservative” scenario, based on military practice, the SMR is permanently integrated into the ship and is not dismantled or transported. The cost and economic elements of this scenario are:

CAPEX: \$600–800 million USD per ship (3–4x the cost of an Ultramax)

OPEX: \$0.05 USD/ton-mile (due to zero bunkering & maintenance)

CO₂ emissions: 0 (full exemption)

ETS cost: €0 (zero exposure)

TCE: ~\$20,500/day

ROI: ~6–8% over 20–25 years

Break-even: >15 years

The weaknesses of the scenario are that the CAPEX is unrealistic for Supramax/Ultramax type ships. It mainly concerns Capesize and larger ships (>150,000 DWT), there is no insurance coverage (nuclear marine liability), there is a significant risk of port dumping (NIMBY), while finally, there is a regulatory gap as the IMO has not established a "Code for Nuclear Merchant Ships".

If the reactors are used as Transferable SMR (Transferable Reactor on 3–4 ships), the SMR is integrated into a modular unit and transferred to another shipbuilding when the old ship completes its life cycle (approximately every 20–25 years) serving 3 or 4 consecutive ships during its lifetime (60–80 years). The cost and financial figures (Amortized) of the scenario are significantly improved:

Amortized CAPEX:

3 ships: \$600M / 3 = \$200M per ship

4 ships: \$600M / 4 = \$150M per ship

OPEX: \$0.04–0.05 USD/ton-mile

CO₂ emissions: 0

ETS cost: €0

TCE: ~\$20,500/day (maybe higher due to ESG premiums)

ROI: >10% (15–20 years with a fixed fare)

Break-even: 9–12 years

The advantages are that CAPEX now becomes competitive with ammonia/hydrogen over time, fuel costs are completely eliminated, leading to savings of \$60–120M in 20 years, while there is independence from ETS and geopolitical risks as with this method the ship does not depend on fuel prices, but also on ports for refueling, while it is an ideal scenario for Capesize and fleets with an investment horizon of more than 25 years.

The Single-use SMR case is technologically feasible but economically unviable for the vast majority of shipowners, it concerns only large state or energy

fleets. In contrast, the Transferable SMR approach, provided there is institutional support, is the most strategic decarbonization option with a horizon of 2050–2100, especially in Ultramax and Capesize fleets with fixed-term charters. However, for SMR in any form to be sustainable, a stable international regulatory framework is required from the IMO (in cooperation with the IAEA), state insurance funds or consortia (at least \$2B nuclear liability pool), ports with “green corridor” legal support (Murmansk, Busan, Singapore) and finally, training of crews and managers, based on the SSR-2/1 (IAEA Safety Guide). A proposed strategy for shipowners is the pilot use of SMRs in Capesize >150,000 DWT with flag states and ports of acceptance between 2025–2035 and if proven reliable the use of Modular SMRs with the ability to be transferred to multigenerational fleets between 2035–2050.

Parameter	Single-use SMR	Transferable SMR
CAPEX	\$600–800M	\$150–200M (amortized)
OPEX	~\$0.05/ton-mile	~\$0.04–0.05/ton-mile
ROI	6–8%	>10%
Break-even	>15 years	9–12 years
Insurance Coverage	Not available	Same limitation
Regulatory Framework	Non-existent	Non-existent
Port Acceptance	Limited	Limited
Commercial Flexibility	Low	Moderate (on fixed routes)

Table 6: Comparative Economic Evaluation of the Two S4 Options

4.5 Findings Analysis – Techno-Economic and Regulatory Evaluation of the Four Decarbonization Scenarios

The transition to a “green” shipping future for Supramax and Ultramax bulk carriers requires the assessment of propulsion scenarios based on technology, economic viability, regulatory requirements and operational risk. The economic comparison of the four scenarios highlights significant differences in terms of investment costs (CAPEX), operating costs (OPEX), return on investment (ROI) and ETS compatibility. In particular, LNG is the most economically viable retrofit solution, with a fast payback and moderate CAPEX, while ammonia and hydrogen have significantly higher operating costs due to expensive fuels. The SMR nuclear reactor, despite having a huge initial cost, compensates for the initial high installation cost with zero OPEX and no ETS costs. Furthermore, all scenarios except LNG achieve zero CO₂ emissions. The CII is “A” for Hydrogen, Ammonia and Nuclear SMR, while for LNG it ranges from “B–C”, with a possible downgrade after 2030. EEXI compliance is full for all scenarios, although Hydrogen may have a negative impact due to the weight of the tanks. Regarding the ETS (EU Emissions Trading System), only LNG carries an annual cost, estimated at around €7.2 million per ship until 2035. In terms of technological maturity and infrastructure, LNG is the only technology with a mature infrastructure network and low risk, while Ammonia and Hydrogen are lagging behind in support and require extensive safety certification. The nuclear reactor requires an international legal regime that does not yet exist, with insurance markets currently refusing coverage.

Parameter	S1: LNG	S2: Ammonia	S3: Hydrogen	S4: SMR (Nuclear)
Technology Maturity	High (TRL 9)	Medium (TRL 6–7)	Low (TRL 5–6)	High (in military), Low (commercial use)
Bunkering Ports	>12 major globally	<5 (e.g., Oslo, Houston)	<10 (mainly EU)	2–3 (e.g., Murmansk, Busan)
Safety Risk	Medium	High	High	Very High (nuclear nature)

Table 7: Technological & Infrastructure Readiness by Scenario

Furthermore, fuel price volatility significantly affects the efficiency of the scenarios (except for Scenario S4). SMR presents complete energy independence, as it does not consume conventional fuels, eliminating the risk of geopolitical crises or price fluctuations. Ammonia and Hydrogen are the most vulnerable technologies, with TCE reductions of up to -31% and significant payback extensions (+6.7 to +8.2 years). LNG shows a moderate impact (-22% TCE, +3.1 years), while only Nuclear SMR maintains zero sensitivity, making it ideal for long-term, fuel-free investments.

Scenario	TCE Change (%)	Payback Period Extension
LNG	-22%	+3.1 years
Ammonia	-31%	+6.7 years
Hydrogen	-28%	+8.2 years
SMR	0%	0 years

Table 8: Fuel Price Sensitivity, +50% Price Increase



Figure 2: Fuel Price Sensitivity, +50% Price Increase

The operational flexibility for ships following the S1 scenario is ideal for those operating routes with LNG infrastructure. In particular, the scenario offers a CII premium (5–7%), while these ships are preferred by ESG-sensitive charterers. It is the most "mature" transition for commercial ships today, with comparatively low risk and immediate compliance with CII / EEXI. However, it requires specialized crew and equipment.

Ammonia (S2) is suitable for new ships with "green charters" and a long-term horizon as the installation cost on a new Supramax is \$20–28 million USD, while in a retrofit over \$30 million USD due to the need to redesign the engine and fuel system. In addition, compliance with the IMO targets for 2050 is achieved. The risks of the scenario are the very high toxicity which implies high safety/certification costs. Finally, the infrastructure today is almost non-existent for Supramax bunkering.

Hydrogen (S3) on the other hand, carries a high risk of TCE penalty due to cargo loss (~15%). A reduction of the available cargo volume of ships by up to 15% is required due to volumetric requirements for H₂, while it has not yet been applied to

cargo ships larger than 5,000 DWT. It is mainly suitable for smaller fleets (e.g. Ro-Pax).

Finally, SMR (S4) provides high efficiency, but is inapplicable without an institutional framework and social acceptance. All options require a complete readjustment of fleet management, crew training and upgrades to SEEMP/EMS to comply with EU ETS, CII and EEXI.

Parameter	S1: LNG	S2: Ammonia	S3: Hydrogen	S4: Nuclear SMR – Single-use	S4: Nuclear SMR – Transferable
CAPEX	\$11–15 million	\$30–35 million	\$25–35 million	\$600–800 million	\$150–200 million (amortized)
OPEX	\$0.085/ton-mile	\$0.11–0.13/ton-mile	\$0.105/ton-mile	\$0.05/ton-mile	\$0.04–0.05/ton-mile
ETS Cost	~€500–600K/year	€0	€0	€0	€0
ROI	8–10%	<6%	<5%	6–8% (20–25 years)	>10% (15–20 years)
Payback Period	5–6 years	>10 years	>10 years	>15 years	9–12 years
Advantages	~20–25% reduction in NO _x , SO _x , and CO ₂ emissions	Zero CO ₂ emissions, compatible as E-fuel	Zero emissions, high energy efficiency	Zero emissions, massive autonomy	
Disadvantages	High retrofit cost, requires cryogenic tanks	Toxicity, lack of complete bunkering infrastructure	Complex H ₂ storage, high cost, low energy density	Legal/social barriers, insurance/certification risk	
Notes	Mature technology, good compliance with CII / EEXI	High safety requirements, still under commercial development	Ideal for short distances / Ro-Pax ferries	Requires new IMO framework, not yet commercially available	

Table 9: Summary Assessment of Scenarios



Figure 3: Comparative Evaluation of Fuel Scenarios (S1–S4)

5. Conclusions

5.1 Decarbonization Drivers and Investment Strategies for Dry Cargo Fleets

For investment decisions in decarbonization scenarios, the age of the ship is perhaps the most critical factor, as retrofitting or newbuilding entails significant CAPEX costs, the expected remaining life cycle horizon largely determines the return on investment (ROI) and payback period. For example, ships that are less than 10 years old have greater strategic flexibility. These ships can be retrofitted with technologies such as LNG dual-fuel or upgraded to be "ammonia-ready", without the owner risking non-recovery of the investment. For 5–10 year old ships, retrofitting for LNG or mechanical interventions for EEXI/CII (e.g. EPL + energy-saving devices) can bring operational benefit from a TCE premium of 5–7% for compliance with CII B–C ratings, avoiding ETS fines that will reach €7–10M per ship by 2035. For shipowners with new ships 0–5 years old, building future-fuel ready with dual-fuel LNG with conversion kits to NH₃ or H₂ is the appropriate strategy to follow (Nunes et al., 2023).

For 10–15 year old ships, the decision becomes more critical, as the amortization of investments exceeding \$20–30 million becomes more uncertain and constitutes the "Retrofitting Decision Point". If the ship has good construction specifications (post-2008 shipbuilding), an investment in CII compliance with SEEMP Part III and digital EMS for tracking/optimization with retrofit to LNG dual-fuel can be considered. However, high-CAPEX interventions such as retrofit for Ammonia or Hydrogen should be avoided (they exceed the useful life cycle). Compliance with the minimum requirements (Level D in CII and moderate EEXI) extends the commercial life of the ship until 2030 without the need for technological risks. For ships over 15 years old, a "Runout / Exit Strategy" should be implemented by shipowners, as most technological interventions are considered to have no substantial economic logic. Retrofitting LNG or ammonia is practically unprofitable, as the payback exceeds the remaining life cycle. These ships can only be retained for short-term spot contracts, while gradual withdrawal / scrapping to CII D/E ratings

should be planned before 2026 and capital recycling should be done with orders for "fuel-flexible" newbuilds with low WACC. In some cases, if freight rates are particularly high (e.g. Asia–India routes with low ETS exposure), the ship can be retained with energy improvements (e.g. Mewis duct, hull coating) for 3–5 additional years of operation (Zhou et al., 2023).

Another characteristic that is an important factor in the strategic choice of technology is the size of the fleet, as it directly affects the cost absorption capacity (CAPEX), access to financing on favorable terms, bargaining power with fuel/technology suppliers and the ability to create internal economies of scale (training, bunkering logistics, maintenance). Fleet size therefore determines the strategy, with small fleets following low-risk paths and collaborating with each other (e.g. green pools). Large ones, on the other hand, have the opportunity to experiment and pioneer, shaping the future green infrastructure. Shipowners, for example, with fewer than 5 ships are required to choose conservative options, such as LNG retrofit on existing ships, due to lower CAPEX and more predictable TCE, or participation in "green pools" or leasing programs (with fuel-inclusive charters) and at the same time waiting for institutional maturity of technologies such as H₂/NH₃ before investing. Investment by small shipowners without access to large charterers with green contracts is more risky (Bows-Larkin et al., 2023).

Shipowners with fleets larger than 10 vessels offer flexibility and experimentation, as they can test SMR or Ammonia pilot models on selected new ships, establish internal bunkering/logistics infrastructures, reducing their dependencies, train crews in-house on H₂/NH₃ safety protocols and secure green financing through the Poseidon Principles. The strategic approach they should follow to decarbonize their fleet is to diversify their fleet with a portion of the fleet using LNG, and the remainder using ammonia-ready newbuilds, as well as investing in ESG reporting tools and SEEMP Part III automation.

Furthermore, the choice of decarbonization technology cannot be universal; the tonnage and type of ship determine the operational characteristics, commercial requirements and availability of alternative technologies. The larger the ship, the greater the economic feasibility of technologies with high CAPEX but zero OPEX (e.g. SMR). Conversely, for smaller ships, retrofit or subsidized zero-carbon solutions make more sense. For Supramax / Ultramax ships (50,000–65,000 DWT) more suitable solutions are LNG retrofit or Ammonia-ready newbuilds as, due to their

relatively limited size compared to Capesize, the CAPEX of SMRs is prohibitive. Their capacity also allows the adoption of cryogenic LNG tanks with only 7–10% cargo loss. On the other hand, Ammonia newbuilds provide long-term flexibility if there is sufficient infrastructure by 2035. The proposed strategy for this type of ship is for existing ships to use LNG retrofit, while for ships to be built, ammonia-ready should be selected to comply with the 2050 targets (Rajabi et al., 2022).

For Capesize / Newcastlemax / VLOC ships (>150,000 DWT) the most suitable solution is the nuclear SMR – Transferable, as due to their high energy consumption, these ships are ideal for high-autonomy technologies such as SMRs. In addition, because they operate mainly on fixed deep-sea routes, they have potential access to specialized ports with the ability to accept nuclear ships (e.g. Murmansk, Busan), while the depreciation cost can be shared over 3–4 successive shipbuildings. The strategy recommended to be followed is the exploration of long-term contracts and lobbying for the acceptance of nuclear propulsion through IMO/IAEA.

Finally, Handy / Feeder ships (15,000–45,000 DWT) should choose Hydrogen (fuel cells) as the most suitable solutions by participating in H₂ pilot routes or replacing them with dual-fuel diesel-electric, as for short distances, smaller tonnage ships are suitable for fuel H₂ cells where bunkering volumes are small, given that due to capacity, any loss of cargo from H₂ tanks is significant, while at the same time there are subsidized infrastructures such as in the Baltic and Scandinavia (Jafarzadeh & Utne, 2019).

The technology selection strategy must also take into account not only the technical characteristics of the ship, but also the type of cargo transported and the commercial obligations of the shipowner — mainly spot vs. time charters. The type of cargo and the type of contracts determine the willingness to invest and the acceptance of technological risks. Green fuels become a profitable option only when they are linked to green revenues, contracts, bonuses, financing. Heavy cargo transports (Iron Ore, Coal, Grain, Cement), for example, are usually carried out on fixed routes with long-term time charters, allowing the depreciation stability of technologies such as LNG or SMR. Shippers (e.g. BHP, Rio Tinto) are increasingly emphasizing ESG metrics, offering green contracts (green time charters) on ships with CII A/B. The appropriate strategy for large cargo customers is therefore to invest in ammonia-ready or SMR in the long term and to secure green long-term charters in cooperation with traders (Wang et al., 2023).

For fragile or high-value goods (e.g. Steel Coils, Project Cargo), charterers have a lower tolerance for delays due to bunkering or technical difficulties, while they prefer high propulsion reliability and quiet operation using fuel cells that have a comparative advantage over other fuels, but are limited to shorter routes. However, LNG dual-fuel engines offer maturity and safety for such cargoes. The strategy when transporting such types of goods for short-sea operations is to invest in hydrogen-electric, while for deep-sea operations, the maintenance of an LNG fleet with reduced emissions is advisable.

Furthermore, Spot operators with Spot Market contracts have limited capacity for long-term investments and prefer LNG retrofit or deferred conversion, while Time charterers, especially green cargo operators) are willing to pay a premium for ships with zero-carbon technologies. The strategy for those shipowners operating in the spot market should be to focus on flexibility, retrofit with methanol-ready or LNG, while those seeking long-term contracts should invest in ammonia or SMR once the infrastructure matures (Ma et al., 2022).

Finally, the evolution of shipping technology does not occur in a vacuum, but is closely linked to the cyclical fluctuations of the freight market and the respective phase of the economic cycle. In periods of low freight rates, investments in innovative technologies shrink, while in periods of high market, the "comfort" for strategic moves appears. The phase of the market defines the risk tolerance strategy. Shipowners should map their position in the cycle and adjust their investment plan accordingly, aggressively in the upswing, defensively in the downturn. In conditions of strong demand and high TCE, for example, shipowners have strong cash flow and greater tolerance for CAPEX risk. Technologies such as LNG retrofit and even Ammonia-ready are starting to become viable due to short-term cost coverage, while environmental indicators (CII, ETS) are gaining more commercial value – green ships are chartered first. The strategy chosen is to aggressively invest in zero-carbon technologies, if contracts exist, and to design newbuilds with fuel-agnostic architecture (LNG-ready / Ammonia-ready / SMR-ready).

With low freight rates such as 2015 or Q2 2023, investments in green technologies freeze, as the priority shifts to sustainability. Shipowners with older fleets prefer to extend the life of ships with small interventions (EPL, SEEMP, Energy Devices). The most resilient technologies are low CAPEX retrofit or energy add-ons (e.g. air lubrication, sails, antifouling), while the strategy followed is to suspend major

investments, focus on compliance at the lowest possible cost and wait for regulatory stability.

Finally, in cyclical markets (Cyclical Operators) shipowners who reposition themselves according to the cycle can invest steadily only if they link the technology with future-proofing. Technologies that offer flexibility and low operating costs in all cycles (such as LNG retrofit or SMR-transferable) have an advantage. The strategy followed is the structural diversification of the fleet according to the cycle and investments in modular or dual-fuel architecture (Van Biert et al., 2020).

5.2 Decarbonization Strategy Proposals for Supramax/Ultramax Bulk Carrier Shipowners

The Supramax/Ultramax class is the backbone of the dry bulk segment, with cargo flexibility, an average fleet age of around 10–12 years, and participation in both spot and time charter markets. In this environment, shipowners are challenged to adapt strategies that balance short-term compliance with long-term competitiveness. LNG technology is the only mature solution for retrofitting 5–15 year old vessels, with CAPEX of \$11–15 million and a faster payback period (5–6 years). Despite the disadvantages (methane slip, cargo limitation), it offers a CII B rating, EEXI compliance, and can command premium rates. The proposed strategy for shipowners is to prioritize retrofitting younger ships, less than 12 years old, with dual-fuel LNG systems, securing contracts with green charterers (e.g. Cargill, Trafigura) that reward reduced emissions, and leveraging green financing (Poseidon Principles, Green Loans) for retrofitting.

For ships built after 2027, shipowners should secure “ammonia-ready” propulsion (e.g. MAN B&W dual-fuel) to reduce future conversion costs. Although fuel costs are 2–3 times higher than HFO, CII A ratings and zero emissions offer potentially stable ESG charter rates after 2030. The proposed strategy is to cooperate with shipyards for ammonia-ready vessel orders with long-term flexibility, to secure optional participation in ammonia bunkering pilot projects (Rotterdam, Oslo) and to link to ESG targets to increase the chances of financing and long-term chartering.

The Small Modular Reactors (SMR) technology, although not yet mature for Supramax vessels, is a long-term target with impressive TCO benefits over a 20–30 year period, mainly with the transferable model (1 SMR/3–4 vessels). Especially for visionary shipowners and fleets larger than 10 vessels, this strategy can create energy independence and complete exemption from CO₂ and ETS costs. It is therefore recommended to closely monitor the regulatory progress of the IMO/IAEA, to participate, where possible, in research consortiums for nuclear commercial maritime (e.g. EURATOM projects) and to analyze the feasibility of fixed long-term routes (e.g. Asia–Europe) with legally friendly ports (e.g. Busan, Murmansk).

The volatile course of technology, on the other hand, indicates the need for a "fuel-agnostic" approach. Shipowners should invest in modular propulsion layouts that allow flexibility between LNG, Methanol, Ammonia or Hydrogen over time. It is therefore necessary to cooperate with shipyards for modular engine room design, to select naval technical solutions (e.g. shaft generators, EMS) that allow upgrading without extensive retrofit and to invest in crew training schemes (SEEMP v3, alternative fuels protocols).

For owners with a fleet of more than 5 ships, diversification is a strategic advantage. Part of the fleet can operate with low CAPEX (e.g. LNG retrofits), while other ships focus on green compliance or participation in pilots (e.g. hydrogen or ammonia testbeds). Fleet segmentation by life expectancy and commercial role, commitment of more modern ships to ESG-driven routes or green supply chains, and dynamic CII retention target every 5 years for each segment of the fleet are required.

The transition to green shipping for the Supramax/Ultramax class is therefore neither a one-way nor an immediate one. It is a matter of strategic positioning by fleet, capital, and market. Those shipowners who choose fuel-agnostic routes with green contracts will gain a competitive advantage over those who remain passive.

Period	Technology	Strategy	Target Fleet Segment
2025–2030	LNG, Dual-fuel	Retrofit LNG + CII optimization	Existing fleet <15 years
2030–2035	Ammonia Dual-Fuel	Newbuilds as “Ammonia-ready”	ESG-oriented charterers
Post-2035	Transferable SMRs	Pilot SMR deployment on Capesize fleet	Long-term investors with regulatory support

Table10: Strategic Deployment Timeline by Scenario

Bibliography

- Alamoush, A., & Ölçer, A. (2025). Harnessing cutting-edge technologies for sustainable future shipping. *Maritime Technology and Research*. <https://so04.tci-thaijo.org/index.php/MTR/article/view/277313>
- Alexandropoulos, L. (2022). Carbon intensity indicator (CII) impact assessment on LNG carriers. NTUA Repository. <https://dspace.lib.ntua.gr/xmlui/handle/123456789/56483>
- Alzayed, A. M. T., Sampath, S., & Pilidis, P. (2022). Techno-environmental evaluation of LNG-fuelled gas turbine systems. *Energies*, 15(5), 1764. <https://www.mdpi.com/1996-1073/15/5/1764>
- Babber, S. (2023). The Impact of Decarbonization on the Oil Tanker Ships Market. Erasmus University Rotterdam. <https://thesis.eur.nl/pub/75391/Babber-Sandeep.pdf>
- Baijal, N. (2025). Unveiling the journey of maritime energy efficiency: A deep dive into EEDI, EEXI, CII, and potential regulation enhancements. *International Journal of Maritime Engineering*. <https://www.intmaritimeengineering.org/index.php/ijme/article/view/1309>
- Balcombe, P., Staffell, I., Kerdan, I. G., Speirs, J. F., Brandon, N. P., & Hawkes, A. D. (2021). How can LNG-fuelled ships meet decarbonisation targets? An environmental and economic analysis. *Energy*, 227, 120462.
- Borgström, M. J. H., & Haufe, J. N. (2022). Is the inclusion of shipping emissions into the EU ETS an effective policy for decarbonizing the shipping sector? Copenhagen Business School. https://research-api.cbs.dk/ws/portalfiles/portal/98727285/1563468_Master_Thesis_127744_129086.pdf
- Bortuzzo, V. (2025). Strategie per l'incremento dell'efficienza energetica di navi mercantili in esercizio. University of Trieste. <https://arts.units.it/handle/11368/3107359>
- Bows-Larkin, A., Harwatt, H., & Mander, S. (2023). Decarbonising maritime transport: Strategies, policy frameworks and fleet-level implications. *Journal of Cleaner Production*, 412, 137148.
- Budiyanto, M. A., Putra, G. L., Riadi, A., & Andika, R. (2024). Techno-economic analysis of combined gas and steam propulsion system of LNG carrier. *Energies*, 17(6), 1415. <https://www.mdpi.com/1996-1073/17/6/1415>
- Bui, K. Q., Perera, L. P., & Emblemståg, J. (2022). Life-cycle cost analysis of an innovative marine dual-fuel engine under uncertainties. *Journal of Cleaner Production*, 378, 134201.
- Cames, M., Wissner, N., Defour, S., & Abbasov, F. (2021). Integration of maritime transport in the EU Emissions Trading System. Oeko Institute. <https://www.oeko.de/fileadmin/oekodoc/Integration-of-maritime-transport-in-EU-ETS.pdf>
- De Gavi, A. (2024). Propulsione nucleare per la navigazione commerciale: sfide e prospettive. University of Genoa. <http://unire.unige.it/handle/123456789/9583>
- Deniz, C., & Zincir, B. (2016). Environmental and economical assessment of alternative marine fuels. *Journal of Cleaner Production*, 113, 438-449.
- dos Santos, V. A., Pereira da Silva, P., & Serrano, L. M. V. (2022). The maritime sector and its problematic decarbonization: A systematic review of the contribution of alternative fuels. *Energies*, 15(10), 3571. <https://www.mdpi.com/1996-1073/15/10/3571>
- DNV Maritime. (2022). Maritime Forecast to 2050 – Alternative Fuels and Energy Carriers. <https://www.dnv.com/publications/maritime-forecast-to-2050-2022-233411>
- Dowling, M. (2023). Road Map for the Development of Commercial Maritime Applications of Advanced Nuclear Technology. OSTI. <https://www.osti.gov/biblio/2484282>
- Duong, P. A., Jung, J., & Kang, H. (2024). Nuclear propulsion in cargo ship: A pathway to the future of emission-free shipping? *Journal of Advanced Marine Engineering and Technology*. https://ejamet.org/_PR/view/?aidx=43686&bidx=3944

- Ejder, E. (2025). Decarbonization pathways in maritime transportation: A techno-economic analysis of alternative marine fuels. ITU Repository. <https://polen.itu.edu.tr/items/6c0c5ed2-bc39-4172-ad5e-d63a5fe734cf>
- Elkafas, A. G., Rivarolo, M., Gadducci, E., & Magistri, L. (2022). Fuel cell systems for maritime: A review of commercial products and applications. *Processes*, 11(1), 97. <https://www.mdpi.com/2227-9717/11/1/97>
- Gee, E. (2025). Analyzing the Potential of MCFC-based CO₂ Capture and Storage Onboard Seagoing Vessels. Utrecht University. <https://studenttheses.uu.nl/handle/20.500.12932/48564>
- Girvin, S., & Ulfbeck, V. (2024). *Carbon-Free Shipping and Shipping Carbon: Contracts in Context*. Bloomsbury Publishing.
- Govindan, K., Dua, R., Anwar, A. H. M. M., & Bansal, P. (2024). Enabling net-zero shipping: An expert review-based agenda for emerging techno-economic and policy research. *Transportation Research Part D: Transport and Environment*.
- Hass, B. S. (2014). *Strategies for the Success of Nuclear Powered Commercial Shipping*. Connecticut Maritime Association.
- Hausweiler, J. (2023). Paths forward for sustainable maritime transport: A techno-economic optimization framework for next-generation vessels. DLR Institute. <https://elib.dlr.de/203963/>
- Hirdaris, S., Patel, H., Sofiadi, D., & Diacakis, M. (2024). Potential Use of Nuclear Power in Shipping. EMSA Report.
- Hodge, C. (2022). *Scotland's Net Zero Roadmap: Industrial Decarbonisation Technology Analysis Report*. <https://snzr.co.uk/wp-content/uploads/2023/03/D3.3.1-SNZR-Industrial-Decarbonisation-Technology-Analysis-Report.pdf>
- Huang, S. T., & Tsai, X. Y. (2025). Exploring decarbonized shipping strategies: A multidimensional analysis using the QFD-based method. *Research Square*. <https://www.researchsquare.com/article/rs-6201467/latest>
- International Maritime Organization (IMO). (2020). Fourth IMO GHG Study 2020. <https://www.imo.org/en/OurWork/Environment/Pages/Fourth-IMO-Greenhouse-Gas-Study.aspx>
- International Maritime Organization (IMO). (2023). Carbon Intensity Indicator (CII) – Guidelines on operational carbon intensity reduction. *MEPC.1/Circ.902*. <https://wwwcdn.imo.org/localresources/en/KnowledgeCentre/InDexofIMOResolutions/MEPCDocuments/MEPC.1-Circ.902.pdf>
- Iqbal, R., Zeng, Y., Zeeshan, M., & Zhang, Q. (2024). Comparative techno-economic evaluation of shipboard hybrid systems: A step toward green maritime transportation. *Renewable Energy*, 220, 124587.
- Jafarzadeh, S., & Utne, I. B. (2019). A framework to bridge the energy efficiency gap in shipping. *Energy*, 169, 364–372.
- Jang, H., Park, C., & Jeong, B. (2024). A prospective LCA framework for sustainable renewable fuels in international shipping: Hydrogen-based e-fuels. SSRN. https://papers.ssrn.com/sol3/papers.cfm?abstract_id=5095662
- Juretić, M. (2025). Energetska učinkovitost pogonskih sustava LNG brodova. University of Rijeka Repository. <https://repository.pfri.uniri.hr/islandora/object/pfri:4794>
- Kalajdžić, M., Momčilović, N., & Vasilev, M. (2025). On energy efficiency of tankers: EEDI, EEXI and CII. *Ocean Engineering*, Elsevier.
- Karvounis, P., Dantas, J. L. D., & Tsoumpris, C. (2022). Ship power plant decarbonisation using hybrid systems and ammonia fuel: A techno-economic–environmental analysis. *Journal of Marine Science and Engineering*, 10(11), 1675. <https://www.mdpi.com/2077-1312/10/11/1675>
- Kistner, L., Bensmann, A., & Minke, C. (2023). Comprehensive techno-economic assessment of power technologies and synthetic fuels under discussion for ship applications. *Renewable and Sustainable Energy Reviews*, 176, 113156.

- Kostidi, E., & Lyridis, D. (2025). Customizable Life Cycle Cost Methodology for Ammonia Fuel Storage. *Energies*, 18(5), 1228. <https://www.mdpi.com/1996-1073/18/5/1228>
- Kunze, C. D. (2022). The role of generation IV nuclear reactors in decarbonising international shipping: a multi-criteria decision making (MCDM) framework for matching potential decarbonisation pathways to different ship types and size.
- Laasma, A., Otsason, R., & Tapaninen, U. (2024). Decarbonising coastal ferries: The case of the Estonian state fleet ferry. In *Towards a Zero Carbon Maritime Transport* (pp. 263–284). Edward Elgar Publishing. <https://www.elgaronline.com/edcollchap/book/9781035321469/book-part-9781035321469-14.xml>
- Lahikainen, A. O. E. (2022). Contractual Challenges for Maritime Decarbonisation. Norwegian School of Economics. <https://openaccess.nhh.no/nhh-xmlui/handle/11250/3018304>
- Lee, H., Lee, J., Roh, G., & Choung, C. (2024). Comparative life cycle assessments and economic analyses of alternative marine fuels. *Sustainability*, 16(5), 2114. <https://www.mdpi.com/2071-1050/16/5/2114>
- Liu, W., Xu, B., & Li, J. (2025). Data-driven carbon emission dynamics under ship in-port congestion. *Journal of Marine Science and Engineering*, 13(4), 812. <https://www.mdpi.com/2077-1312/13/4/812>
- Liu, Y. (2025). Advancements and innovations in marine fuel technology. *E3S Web of Conferences*, 525, 01010. https://www.e3s-conferences.org/articles/e3sconf/pdf/2025/06/e3sconf_icnaoe2024_01010.pdf
- Lyridis, D., & Kostidi, E. (2025). Bridging Technical Challenges and Economic Goals: Project Management for Energy Transition in Maritime Retrofitting. *Energies*, 18(4), 804. <https://www.mdpi.com/1996-1073/18/4/804>
- Ma, L., Zhu, Y., & Zhang, Y. (2022). Investment assessment of green shipping under carbon regulation. *Marine Policy*, 143, 105145.
- Mallouppas, G., & Yfantis, E. A. (2021). Decarbonization in Shipping Industry: A Review of Research, Technology Development, and Innovation Proposals. *JMSE*, 9(4), 415. <https://www.mdpi.com/2077-1312/9/4/415>
- Mugabi, J., Kim, S., & Jeong, J. H. (2024). Review of the Regulatory Challenges and Opportunities for Maritime Small Modular Reactors in Republic of Korea. *Journal of Marine Science and Engineering*, 12(11), 1978. <https://www.mdpi.com/2077-1312/12/11/1978>
- Murakami, T., & Anbumozhi, V. (2021). Global Situation of Small Modular Reactor Development and Deployment. ERIA. <https://www.eria.org/uploads/media/Research-Project-Report/2021-07-Small-Modular-Reactor-/Global-Situation-Small-Modular-Reactor-Development-Deployment.pdf>
- Nasir, H., & Tian, T. (2024). A Comparative Study on Alternative Marine Fuels: Economic, Technology, Environmental and Safety Issues. Chalmers University. <https://odr.chalmers.se/items/800e70a5-71b9-4ff4-bc9c-d76f728c2238>
- Nasirudin, A., Utama, I. K. A. P., & Aryawan, W. D. (2024). The Contribution of Energy Efficiency and Decarbonization: Case of a 6,500-Ton DWT Tanker Ship with Different Sail Systems. *IEEE Xplore*. <https://ieeexplore.ieee.org/document/10795577>
- Niemi, J. (2025). Integration of Hydrogen Fuel Cells in Marine Power Systems. Tampere University. <https://trepo.tuni.fi/bitstream/handle/10024/225375/NiemiJoonas.pdf>
- Nikolopoulos, L., & Boulougouris, E. (2023). Simulation-Driven Robust Optimization for Design of Zero-Emission Vessels. *Energies*, 16(12), 4731. <https://www.mdpi.com/1996-1073/16/12/4731>
- Nunes, B., Pinheiro, L., & Barbosa, J. (2023). The impact of ship age on energy efficiency and carbon taxation. *Transportation Research Part D: Transport and Environment*, 118, 103573.
- Olsen, P. K. (2023). Decision support for renewal and retrofitting of offshore supply vessels. NTNU. <https://ntnuopen.ntnu.no/ntnu-xmlui/handle/11250/3094575>

- Pakkanen, P., & Vettor, R. (2023). Decarbonization Support from Digital Solutions Providers. In *Maritime Decarbonization: Practical Tools* (pp. 573–589). Springer. https://link.springer.com/chapter/10.1007/978-3-031-39936-7_29
- Park, C., Hwang, I., Jang, H., Jeong, B., & Ha, S. (2024). Comparative analysis of marine alternative fuels for offshore supply vessels. *Applied Sciences*. <https://strathprints.strath.ac.uk/91327/>
- Piccardo, S. (2025). Innovative Technologies and Low-Impact Alternative Fuels for Maritime Sector Decarbonisation. PhD Thesis, University of Genoa. <https://tesidottorato.depositolegale.it/handle/20.500.14242/210835>
- Piccolo, V. (2023). GHG Emissions From Shipping: How to Overcome Persistent Challenges. National University of Singapore – Working Paper. <https://law.nus.edu.sg/cml/wp-content/uploads/sites/8/2023/07/CML-WPS-2306.pdf>
- Pio, G., Zanobetti, F., Jafarzadeh, S., & Ortiz, M. M. (2023). Sustainability assessment of alternative power systems in maritime transport. *Journal of Cleaner Production*, 421, 138916.
- Prastowo, H., Pitana, T., & Artana, K. B. (2024). Evaluation of Carbon Intensity Index for Ship with Recommended Actions. *International Review of Mechanical Engineering*. <https://scholar.its.ac.id/en/publications/evaluation-of-carbon-intensity-index-for-ship-with-recommended-ac>
- Radica, G., Vidović, T., Šimunović, J., & Jurić, Z. (2025). Overview of hybrid marine energy system configurations and system component modeling approaches. *Energies*, 18(5), 1189. <https://www.mdpi.com/1996-1073/18/5/1189>
- Rajabi, A., Mohammadi, M., & Rahbari, M. (2022). Assessment of nuclear propulsion for merchant shipping: Economic, safety, and infrastructure analysis. *Renewable and Sustainable Energy Reviews*, 165, 112596.
- Rayner, J. (2025). *Image and Identity: Sea Power and Submarine*. University of York. Retrieved from: <https://eprints.whiterose.ac.uk/id/eprint/224114>
- Ringbom, H., & Finska, L. (2022). Regulation of GHGs from ships – On the available discretion for regulatory solutions in a European and Finnish perspective. UiT Arctic University of Norway. <https://munin.uit.no/bitstream/handle/10037/28753/article.pdf?sequence=2>
- Roland, V. J. H. (2023). Applicability of the existing nuclear liability conventions to different types of small modular reactors. *Nuclear Law Bulletin*, 113. <https://heinonline.org/HOL/PDF?handle=hein.journals/nuclb113>
- Sahakyan, M. (2024). *Routledge Handbook of Chinese and Eurasian International Relations*. Routledge. <https://books.google.com/books?hl=en&id=d8MOEQAAQBAJ>
- Schinas, O., & Butler, M. (2016). Feasibility and commercial considerations of LNG-fueled ships. *Ocean Engineering*, 122, 84–96.
- Sharma, N. (2019). *IMO 2020 sulfur cap: Green investment in the shipping industry*. World Maritime University Dissertations. https://commons.wmu.se/all_dissertations/1225/
- Serris, M., Iakovidis, I., & Dimitrellou, S. (2023). Techno-Economic and Environmental Evaluation of a Solar Energy System on a Ro-Ro Vessel. *Energies*, 16(18), 6523. <https://www.mdpi.com/1996-1073/16/18/6523>
- Tvedten, I. Ø., & Bauer, S. (2022). *Retrofitting towards a greener marine shipping future*. *Energy Research & Social Science*, 90, 102619. <https://doi.org/10.1016/j.erss.2022.102619>
- Van Biert, L., Godjevac, M., Visser, K., & Aravind, P. V. (2020). A review of fuel cell systems for maritime applications. *Journal of Power Sources*, 327, 345–364.
- Vidović, T., Šimunović, J., Radica, G., & Penga, Ž. (2023). Systematic overview of newly available technologies in the green maritime sector. *Energies*, 16(2), 641. <https://www.mdpi.com/1996-1073/16/2/641>

- Vinoya, C. L., Ubando, A. T., & Culaba, A. B. (2023). State-of-the-art review of small modular reactors. *Energies*, 16(7), 3224. <https://www.mdpi.com/1996-1073/16/7/3224>
- Wang, Z., Chen, Y., & Yang, D. (2023). Charter contracts, technological flexibility, and investment risk in decarbonized shipping. *Marine Policy*, 148, 105387.
- Wang, Z., Dong, B., Liu, H., & Han, F. (2024). Analysis and evaluation of fuel cell technologies for sustainable ship power: Energy efficiency and environmental impact. *Energy Conversion and Management*.
- Wang, C., Peng, Z., Yang, J., Zhang, N., & Li, K. (2025). Optimal alternative fuel selection for dual-fuel ships under FuelEU Maritime regulations. *Journal of Marine Science and Engineering*, 13(6), 1105. <https://www.mdpi.com/2077-1312/13/6/1105>
- Wu, Y. (2024). Large-scale optimization for shipping operations management. The Hong Kong Polytechnic University. <https://theses.lib.polyu.edu.hk/handle/200/13027>
- Yuksel, O., Pamik, M., & Bayraktar, M. (2025). The assessment of alternative fuel and engine power limitation utilisation in hybrid marine propulsion systems. *Journal of Marine Engineering & Technology*.
- Zamboni, G., Scamardella, F., Gualeni, P., & Canepa, E. (2024). Comparative analysis among different alternative fuels for ship propulsion. *Heliyon*, 10(2), e20899.
- Zeya, S. S. (2022). Roadmap to Hydrogen-powered vessels in the EU by 2030. Erasmus University. <https://thesis.eur.nl/pub/64886/Zeya-Syed-Sharique.pdf>
- Zhang, Z., Zheng, X., Cui, D., & Yang, M. (2025). Research Progress of Fuel Cell Technology in Marine Applications: A Review. *Journal of Marine Science and Engineering*.
- Zhaka, V., & Samuelsson, B. (2024). Hydrogen as fuel in the maritime sector: From production to propulsion. *Energy Reports*. <https://www.sciencedirect.com/science/article/pii/S2352484724007261>
- Zhou, H., Lin, J., & Wang, S. (2023). Economic and environmental analysis of ammonia-powered ships: Retrofit versus newbuilds. *Energy Reports*, 9, 1123–1136.